View NSN Online: https://aerobasegroup.com/nsn/8030-00-560-8756

Product ID:PR-148 MSDS Date:01/01/1987 FSC:8030 NIIN:00-560-8756 **MSDS Number: BFFMJ** === Responsible Party === Company Name: COURTAULDS AEROSPACE INC Address:757 CALIFORNIA ST Box:1800 **City:GLENDALE** State:CA ZIP:91203 Country:US Info Phone Num:818-549-7973 Emergency Phone Num:818-549-7973 CAGE:83574 === Contra ctor Identification === Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY Address:5430 SAN FERNANDO RD Box:1800 City:GLENDALE State:CA ZIP:91209 Country:US Phone:818-240-2060 CAGE:83574 Ingred Name:NAPTHEA Fraction by Wt: 48.0% ACGIH TLV:200 OOM Ingred Name: METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 17.0% OSHA PEL:200 PPM/300 STEL ACGIH TLV:200 PPM/300S

TEL 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:ISOPROPYL ALCOHOL (SARA III) CAS:67-63-0 RTECS #:NT8050000 Fraction by Wt: 8.0% OSHA PEL:400 PPM/500 STEL ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:ETHYL ACETATE (SARA III) CAS:141-78-6 RTECS #:AH5425000 Fraction by Wt: 17.0% OSHA PEL:400 PPM ACGIH TLV:400 PPM; 9192 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name:ORGANIC TITANATE Fraction by Wt: < 3%

Ingred Name:VOC. G/L (LESS EXEMPTIONS): 795.73 RTECS #:9999999VO Other REC Limits:NONE SPECIFIED

Effects of Overexposure:EYE,SKIN IRRITANT;EYES:CONJUNCTIVITIS;INHALATION MAY CAUSE DIZZINESS,NAUSEA.

First Aid:SKIN:WASH W.SOAP & H*20. EYES:FLUSH W. H*20. INGESTED:DON'T INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE ANYTHING BY M OUTH TO UNCONSCIOUS PERSON.

Flash Point:23 F, -5 C PMCC Lower Limits:1.9 Upper Limits:9.0 Extinguishing Media:FOAM, CO*2, DRY CHEMICAL Fire Fighting Procedures:WEAR AIR-SUPPLIED RESPIRATOR WHEN FIGHTING FIRES. Unusual Fire/Explosion Hazard:MAY BE IGNITED BY HEAT,FLAME,IGNITION SOURCES.

Spill Release Procedures: STOP LEAK W/O RISK.ELIMINATE IGNITION

SOURCES.KEEP UNPROTECTED PERSONS AWAY FROM AREA.ABSORB SPILL WITH TOWELS,RAGS OR OTHER ABSORBENT MATL.LG SPILL:DIKE AREA,PUMP TO SALVAGE TANK.PLACE ABSORBED MATL IN CLOSED CONTAINERS.

Handling and Storage Precautions:STORE IN TIGHTLY CLOSED CONTAINERS IN COOL DRY AREA.AVOID FIRE HAZARDS.PROTECT FROM PHYSICAL DAMAGE.

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:AIR -SUPPLIED RESPIRATOR IN ENCLOSED AREAS. Ventilation:LOCAL OR MECHANICAL TO MINIMIZE VAPORS Protective Gloves:RUBBER Eye Protection:CHEMICAL GOGGLES Other Protective Equipment:PROTECTIVE HAND CREAM. Supplemental Safety and Health MSDS DATED 8-29-86,THIS MSDS PREPARED BY CHEM.COMMODITIES;FOR INFORMATION,CONTACT PHONE:714-864-2310

HCC:F2 Boiling Pt:B.P. Text:171 F, 77C Vapor Pres:60 Vapor Density:3.0 Spec Gravity:1.32 Evapor ation Rate & amp; Reference:> BUTYL ACETATE Appearance and Odor:BLUE LIQUID,AROMATIC NAPHTHA ODOR. Percent Volatiles by Volume:98.0

Stability Indicator/Materials to Avoid:YES AVOID STRONG OXIDIZERS,BASES,ACIDS. Stability Condition to Avoid:AVOID IGNITION/HEAT SOURCES. Hazardous Decomposition Products:MAY FORM TOXIC MATL;CO*2,CO,VARIOUS HYDROCARBONS.

Waste

Disposal Methods:STORE IN APPROVED STORAGE CONTAINERS AND DISPOSE IN ACCORDANCE WITH LOCAL,STATE,AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek compete nt professional advice to verify and assume responsibility for the suitability of this information to their particular situation.