

AMERON INDUSTRIAL COATINGS DIVISION -- OLIVE DRAB # 24087 -- 8010-00-577-4381

=====  
Product Identification  
=====

Product ID:OLIVE DRAB # 24087

MSDS Date:01/01/1985

FSC:8010

NIIN:00-577-4381

MSDS Number: BFFTS

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Emergency Phone Num:316-733-1361

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATIN

GS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHYL BENZENE (SARA III)

CAS:100-41-4

RTECS #:DA0700000

Fraction by Wt: 3.0%

OSHA PEL:100 PPM/125 STEL

ACGIH TLV:100 PPM/125STEL 9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

RTECS #:NP9625000

Fraction by Wt: 10.0%

OSHA PEL:100 PPM

ACGIH TLV:50 PP

M; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)  
CAS:8030-30-6  
RTECS #:SE7555000  
Fraction by Wt: 26.0%  
OSHA PEL:100 PPM

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR  
1910.1025),(CRO3 CEILING 0.1 MG/M3)  
CAS:7758-97-6  
RTECS #:GB2975000  
Fraction by Wt: 13.0%  
OSHA PEL:0.05 MG/M3 (PB)  
ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:LEAD TETROXIDE (RED LEAD), (OSHA PEL FROM 29CFR 1910.1025)  
CAS:1314-41-6  
RTECS #:OG5425000  
Fraction by Wt: 6  
.0%  
OSHA PEL:0.05 MG/M3 (PB)  
ACGIH TLV:0.15 MG/M3(PB); 8990

=====  
Hazards Identification  
=====

Effects of Overexposure:ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE  
NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION.

=====  
First Aid Measures  
=====

First Aid:IN CASE OF CONTACT-FLUSH SKIN AND EYES WITH WATER AND REMOVE  
CONTAMINATED CLOTHING. IF INHALED-REMOVE TO FRESH AIR. CALL A  
PHYSICIAN IF CONDITIONS PERSIST.

=====  
Fire Fighting Measures  
=====

Flash Point:60F TCC  
Lower Limits:1.0  
Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE  
FIRES-FOAM  
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID  
BREATHING VAPORS. REMOV

E WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE-FALL OF LIQUID IN EXCESS OF A FEW INCHES.

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY

Supplemental Safety and Health

RESPIRATOR USE BASED ON CHEM CONC. AND CONDITIONS OF USE

=====  
Physical/Chemical Properties  
=====

HCC:F2

Boiling Pt:B.P. Text:223-284F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:61.0

=====  
Stability and Reactivity Data  
=====

Stability Indicator

Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRE, HEAT AND HOT SURFACES.

=====  
Disposal Considerations  
=====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever

er,  
expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.