

NATIONAL AEROSOL PRODUCTS(DIST)DEVOE&RAYNOLDS(MFR) -- DR039 FLAT ACRYLIC LACQUER #37038 -- 8010-00-582-5382

=====  
Product Identification  
=====

Product ID:DR039 FLAT ACRYLIC LACQUER #37038

MSDS Date:01/01/1985

FSC:8010

NIIN:00-582-5382

MSDS Number: BFGGM

=== Responsible Party ===

Company Name:NATIONAL AEROSOL PRODUCTS(DIST)DEVOE&RAYNOLDS(MFR)

Address:2193 E 14TH ST

City:LOS ANGELES

State:CA

ZIP:90

021-2843

Country:US

CAGE:5N005

=== Contractor Identification ===

Company Name:NATIONAL AEROSOL PRODUCT

Address:2193 E 14TH ST

Box:City:LOS ANGELES

State:CA

ZIP:90021-2843

Country:US

CAGE:5N005

=====  
Composition/Information on Ingredients  
=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 2.90%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 24.0%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)  
CAS:108-10-1  
RTECS #:SA9275000  
Fraction by Wt: 21.0%  
OSHA PEL:100 PPM/75 STEL  
ACGIH TLV:50 PPM/75 STEL; 9293  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 19.0%  
OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 P  
PM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:2-BUTOXYETHANOL  
CAS:111-76-2  
RTECS #:KJ8575000  
Fraction by Wt: 7.0%  
OSHA PEL:S, 50 PPM  
ACGIH TLV:S, 25 PPM; 9293

=====  
===== Hazards Identification =====

Effects of Overexposure:INHAL:HEADACHE,NAUSEA,DIZZINESS,SKIN  
CONTACT:PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION.

=====  
===== First Aid Measures =====

First Aid:INHAL:MOVE TO FRESH AIR.SKIN CONTACT-FL

USH W/LG AMOUNTS OF  
WATER.REMOVE CONTAMINATED CLOTHING.EYE CONTACT-FLUSH W/CLEAN WATER  
FOR AT LEAST 15 MIN.CALL PHYSICIAN.

===== Fire Fighting Measures =====

Flash Point:43 F PMCC  
Extinguishing Media:CARBON DIOXIDE,DRY CHEMICAL,FOAM  
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS TO BE WORN  
BY FIREFIGHTER  
Unusual Fire/Explosion Hazard:WATER SHOULD BE USED TO COOL CONTAINERS  
EXPOSED TO FIRE

===== Accidental Release Mea  
sures =====

Spill Release Procedures:AVOID BREATHING VAPORS,EXTINGUISH IGNITION  
SOURCE IN IMMEDIATE AREA.AVOID CONTACT W/LIQUID -MFR RECOMMENDATION

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPERATURES  
Other Precautions:CLOSE CONTAINERS AFTER USE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR DEVICE IN  
CONF  
NED AREAS.  
Ventilation:SUFFICIENT LOCAL EXHAUST TO KEEP CONCENTRATION BELOW TLV  
Protective Gloves:SOLVENT RESIST  
Other Protective Equipment:NORMAL PROTECTIVE CLOTHING  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V3  
Boiling Pt:B.P. Text:176-343F  
Spec Gravity:1.04  
Evaporation Rate & Reference:SLOWER THAN ETHER  
Solubility in Water:SLIGHT  
Appearance and Odor:BLACK,MOBILE LIQUID CONTAINING VOLATILE SOLVENTS.  
Percent Volatiles by Volume:

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

OXIDIZING MATERIALS, SOFTENS RUBBER

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN CLOSED CONTAINERS AWAY FROM  
IGNITION SOURCES. -MFR RECOMMENDATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated

for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.