

DEVOE & RAYNOLDS CO., INC. -- DR039-CONCENTRATE -- 8010-00-582-5382

=====
Product Identification
=====

Product ID:DR039-CONCENTRATE

MSDS Date:01/01/1987

FSC:8010

NIIN:00-582-5382

MSDS Number: BFGGP

=== Responsible Party ===

Company Name:DEVOE & RAYNOLDS CO., INC.

Emergency Phone Num:714-686-6950

CAGE:EO559

=== Contractor Identification ===

Company Name:DEVOE & RAYNOLDS CO, INC.

Box:7600

CAGE:EO55

9

Company Name:DEVOE COATINGS CO DIV OF GROW GROUP INC

Address:2625 DURAHART ST

Box:City:RIVERSIDE

State:CA

ZIP:92507-2606

Country:US

CAGE:70506

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 24%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 29%

OSHA PE

L:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 21%
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:2-BUTOXYETHANOL
CAS:111-76-2
RTECS #:KJ8575000
Fraction by Wt: 7.0%
OSHA PEL:S, 50 PPM
ACGIH TLV:S, 25 PPM; 9293

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:E
L6475000
Fraction by Wt: 19%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:INHALATION-HEADACHE, NAUSEA, DIZZINESS. SKIN
CONTACT-PROLONGED OR REPEATED CONTACT MAY IRRITATE SKIN

=====
===== First Aid Measures =====

First Aid:INHALATION-MOVE TO FRESH AIR. SKIN-FLUSH WITH LARGE AMOUNTS
OF WATER. REMOVE CONTAMINAT

ED CLOTHING. EYE CONTACT- FLUSH WITH
CLEAN WATER FOR AT LEAST 15 MINUTES. CALL A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:43F; 6.1C PMCC
Extinguishing Media:CO*2; DRY CHEMICAL; FOAM
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS
Unusual Fire/Explosion Hazard:WATER SHOULD BE USED TO COOL CONTAINERS
EXPOSED TO FIRE.

=====
Accidental Release Measures
=====

Spill Release Procedures:AVOID BREA
THING VAPORS, EXTINGUISH IGNITION
SOURCES IN IMMEDIATE AREA. AVOID CONTACT WITH LIQUID.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPERATURES.
Other Precautions:CLOSE CONTAINERS AFTER USE.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:IN CONFINED AREAS, USE U.S. BUR. OF MINES
APPROVED RESPIRATOR.
Ventilation:LOCAL-SUFFICIENT TO KEEP CONCENTRATION BELOW GIV
EN TLV.
Protective Gloves:YES
Eye Protection:SOLVENT RESISTANT
Other Protective Equipment:NORMAL PROTECTIVE CLOTHING
Supplemental Safety and Health
BOILING POINT RANGE:- 80-173C

=====
Physical/Chemical Properties
=====

HCC:V3
Boiling Pt:B.P. Text:176-343F
Vapor Density:>1
Spec Gravity:1.04
Evaporation Rate & Reference: