View NSN Online: https://aerobasegroup.com/nsn/8010-00-584-2953

SEAGRAVE COATING CORP CHEMRAY DIVISION -- F-120,MIL-P-L5930,VINYL CHROMATE PAINT -- 8010-00-584-2953

============= Product Identification ========================

Product ID:F-120,MIL-P-L5930,VINYL CHROMATE PAINT

MSDS Date:01/01/1985

FSC:8010

NIIN:00-584-2953 MSDS Number: BFGJY

=== Responsible Party ===

Company Name: SEAGRAVE COATING CORP CHEMRAY DIVISION

Address: 209 N MICHIGAN AVE

City:KENILWORTH

State:NJ ZIP:07033 Country

:US

Info Phone Num:201-245-1111

Emergency Phone Num:201-245-1111

CAGE:8D124

=== Contractor Identification ===

Company Name: SEAGRAVE COATING CORP CHEMRAY DIVISION

Address: 209 N MICHIGAN AVE

Box:City:KENILWORTH

State:NJ ZIP:07033 Country:US

Phone:201-245-1111

CAGE:8D124

======= Composition/Information on Ingredients ========

Ingred Name: METHYL ISOBUTYL KETONE (SARA III)

CAS:108-10-1

RTECS #:SA9275000

OSHA PEL:100 PPM/75 STEL ACGIH TLV:50 PPM/75 STEL; 9293

EPA Rpt Qty:5000 LBS

DOT R

pt Qty:5000 LBS Ingred Name: TOLUENE (SARA III) CAS:108-88-3 RTECS #:XS5250000 OSHA PEL:200 PPM/150 STEL ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ingred Name:TRICRESYL PHOSPHATE 8W/VINYL CHLORIDE-VINYLACETATE COPOLYMER THEY FORM 20% OF PRODUCT) ACGIH TLV:0.1 MG/CUM Ingred Name: VINYL CHLORIDE VINYL ACETATE COPOLYMER (W/TRICRESYL PHOSPHATE THEY FORM 20% OF PRODUCT) ACGIH TLV:0.1 MG/CUM Ingred Name: ZINC CHROMATE CAS:13530-65-9 RTECS #:GB3290000 OSHA PEL:0.1 MG/M3 (CRO3) ACGIH TLV:0.01MG/M3(CR)A1;9192 ========== Hazards Identification =============== Effects of Overexposure: MAY IRRIT SKIN/RESP SYS. OVER INH MAY CAUSE LOWERING OF BODY TEMP. HEAT/RESP RATE. First Aid:FLUSH EXPOSED SKIN FREELY W/WATER, CALL MD IF NEC. IF OVER INH OCCURS, REMOVE TO WELL-VENT AREA. Flash Point:45F TOC Lower Limits:1.2 **Upper Limits:7.5** Extinguishing Media:DRY CHEM, CO*2 Fire Fighting Procedures: WATER SPRAY MAY BE INEFF AS EXTINGUISHING **AGENT** Unusual Fire/Explosion Hazard: VAPORS CAN TRAVEL GREAT DISTANCE & FLASH **BACK TO ORIGIN** ======== Accidental Release Measures ============= Spill Release Procedures: FOLLOW GEN CLEANING PROCEDURES. SM SPILLS MAY BE WASHED AWAY W/WATER, MFR REC. ============= Handling and Storage ==========================

Handling and Storage P

recautions:STORE IN COOL, DRY PLACE AWAY FROM
OPEN FLAMES & PHYSICAL ABUSE & W/GOOD VENT.

Other Precautions:ODOR THRESHOLD NOT SUFFICIENT TO WARN OF DANGEROUS CONC. SECURE ALL SOURCES OF IGNITION. KEEP CNTNRS CLOSED AS MUCH AS POSS.

====== Exposure Controls/Personal Protection ========

Respiratory Protection: SELF-CNTND BRTHNG APPARATUS, NIOSH/MSHA APPRVD

Ventilation: USE LOCAL & MECH EXHST

Protective Gloves:YES Eye Protection:YES Supplemental Safety and Health

LMPBLCK,

MG-S10*4& ZN-CRO4 FORM 15%.AL STERATE