

BORDEN, CONSUMER PRODUCTS DIVISION -- KRYLON 1605 -- 8010-00-584-3151
===== Product Identification =====

Product ID:KRYLON 1605

MSDS Date:12/04/1986

FSC:8010

NIIN:00-584-3151

MSDS Number: BFGNR

=== Responsible Party ===

Company Name:BORDEN, CONSUMER PRODUCTS DIVISION

Address:180 E BROAD ST

City:COLUMBUS

State:OH

ZIP:43215-3705

Country:US

Emergency Phone Num:614-431-6600

CAGE:EO239

=== Contractor

Identification ===

Company Name:BORDEN INC

Address:180 E BROAD ST

Box:208

City:COLUMBUS

State:OH

ZIP:43215-3705

Country:US

Phone:614-225-6124

CAGE:07982

Company Name:BORDEN, CONSUMER PRODS. DIV., DIV. OF BORDENS INC.

Address:180 EAST BROAD STREET

Box:City:COLUMBUS

State:OH

ZIP:43215-3705

Country:US

Phone:614-431-6680

CAGE:EO239

Company Name:CONSOLIDATED CONTROLS CORPORATION

CAGE:09790

===== Composition/Information on Ingredients =====

Ingred Name:ACETONE (SARA III)

CAS:67-64

-1

RTECS #:AL3150000
Fraction by Wt: 30-50%
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-BUTYL ALCOHOL (SARA III)
CAS:71-36-3
RTECS #:EO1400000
Fraction by Wt: 1-5%
OSHA PEL:100 PPM
ACGIH TLV:S, C 50 PPM; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 15-30%
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:
78-93-3
RTECS #:EL6475000
Fraction by Wt: 15-30%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)
CAS:108-10-1
RTECS #:SA9275000
Fraction by Wt: 1-5%
OSHA PEL:100 PPM/75 STEL
ACGIH TLV:50 PPM/75 STEL; 9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:ACEDIC ACID, 2-METHOXY-1-METHYLETHYL ESTER.
CAS:108-65-6
RTECS #:AI8925000
Fraction by Wt: 5-15%

Ingred Name:TOLUENE (SARA III)
CAS:108-88-

3

RTECS #:XS5250000

Fraction by Wt: 1-5%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 5-15%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO

Reports of Carcinogenicity:NTP:NO I

ARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHALATION: MAY BE HARMFUL. LIQUID OR VAPOR CAN CAUSE IRRITATION OF NOSE, THROAT AND LUNGS. SKIN: CAUSES IRRITATION. EYES: CAUSES IRRITATION.

Effects of Overexposure:CENTRAL NERVOUS SYSTEM DEPRESSION, HEADACHE, DIZZINESS, NAUSEA, VOMITING, UNCONSCIOUSNESS AND EVEN ASPHYXIATION.

Medical Cond Aggravated by Exposure:SKIN & LUNG DISORDERS.

=====
===== First Aid Measures =====

First Aid:SKIN: IMMEDIATELY FLU

SH WITH WATER, IF IRRITATION PERSISTS,

GET MEDICAL HELP. EYES: FLUSH WITH PLENTY OF WATER FOR 15 MINUTES,

GET MEDICAL ATTENTION. INGESTION: DILUTE BY DRINKING LARGE

QUANTITIES OF WATER. GET MEDICAL ATTENTION IMMEDIATELY.

INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, GIVE CPR. IF

BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Flash Point:N/R (AEROSOL)

Extinguishing Media:DRY CHEMICAL, FOAM OR

CO*2.

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE AS EXTINGUISHING MEDIA, BUT SHOULD BE USED TO KEEP FIRE-EXPOSED CONTAINERS COOL. WEAR NIOSH APPROVED SCBA.

Unusual Fire/Explosion Hazard:EXPOSURE TO HIGH TEMPERATURE MAY CAUSE BURSTING. AVOID RADIATORS, STOVES, DIRECT SUNLIGHT, OR OTHER HEAT SOURCE.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL IGNITION SOURCES. SOAK UP WITH ABSORBENT MATERIAL & REMOVE TO A CHEMICAL DISPOSAL AREA. PREVENT ENTRY INTO NATURAL BODIES OF WATER.

Neutralizing Agent:NONE

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT TEMPERATURES OVER 120F.

Other Precautions:IF AIRBORNE CONTAMINATES ARE GENERATED WHEN THE MATERIAL IS HEATED OR HANDLED, SUFFICIENT VENTILATION IN VOLUME AND AIR FLOW PATTERNS SHOULD BE PROVIDED TO KEEP AIR CONTAMINANT CONCENTRATION LEVELS BE LOW ACCEPTABLE CRITERIA.

=

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATORY PROTECTION. SELECT RESPIRATOR IN ACCORDANCE WITH OSHA 29 CFR 1910.134 OR OTHER APPLICABLE STANDARDS OR GUIDE LINES

Ventilation:LOCAL EXHAUST VENTILATION RECOMMENDED TO MINIMIZE EMPLOYEE EXPOSURE.

Protective Gloves:IMPERVIOUS GLOVES AS REQUIRED

Eye Protection:GOGGLES WHERE CONTACT IS LIKELY

Other Protective Equipment:APRON & FULL LENGTH WORK CLOTHING.

Work Hyg

enic Practices:HANDLE IN ACCORDANCE WITH GOOD INDUSTRIAL HYGIENE AND SAFETY PRACTICES. AVOID UNNECESSARY EXPOSURE & WASH THOROUGHLY.

Supplemental Safety and Health

NONE

===== Physical/Chemical Properties =====

HCC:V3

Vapor Density:>1

Spec Gravity: