

L.D. CAULK CO.,DIV OF DENTSPLY INTERNATIONAL -- LUCITONE LIQUID -- 6520-00-584-5965

=====
Product Identification
=====

Product ID:LUCITONE LIQUID

MSDS Date:01/01/1985

FSC:6520

NIIN:00-584-5965

MSDS Number: BFGRP

=== Responsible Party ===

Company Name:L.D. CAULK CO.,DIV OF DENTSPLY INTERNATIONAL

Address:LAKEVIEW AND CLARKE AVE

Box:359

City:MILFORD

State:DE

ZIP:19963

Country:US

CAGE:KO453

=== Contr

actor Identification ===

Company Name:CAULK/DENTSPLY

Address:38 W CLARKE AVE

Box:359

City:MILFORD

State:DE

ZIP:19963-0359

Country:US

Phone:302-422-4511/ 703-451-1900

CAGE:11107

Company Name:L.D. CAULK CO.,DIV OF DENTSPLY INTERNATIONAL

Address:LAKEVIEW AND CLARKE AVE

Box:359

City:MILFORD

State:DE

ZIP:19963

Country:US

CAGE:KO453

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL METHACRYLATE (SARA III)

CAS:80-62-6

RTECS #:OZ5075000

Fraction by Wt: 92.5%

OSHA

PEL:100 PPM
ACGIH TLV:100 PPM; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingrid Name:ETHYLENE GLYCOL DIMETHACRYLATE INHIBITED
CAS:97-90-5
RTECS #:OZ4400000
Fraction by Wt: 7.5%

=====
Hazards Identification
=====

Effects of Overexposure:VAPOR: HEADACHE,EYE/LUNG IRRITATION. EYE/SKIN CONTACT: CORNEAL DAMAGE,IRRITATION.

=====
First Aid Measures
=====

First Aid:INHALATION: REMOVE TO FRESH AIR,GIVE ARTIFICIAL RESPIRATION
IF NEEDED,CONSULT PHYSICIAN. EYE: FLUSH WITH WATER 15 MINUTES,CONSULT PHYSICIAN. SKIN: WASH WITH SOAP AND WATER.

=====
Fire Fighting Measures
=====

Flash Point:50F/10C (FCC)
Lower Limits:2.1
Upper Limits:12.5
Extinguishing Media:FOAM,CARBON DIOXIDE,DRY CHEMICAL
Fire Fighting Procedures:SELF-CONTAIN BREATH APP

=====
Accidental Release Measures
=====

Spill Release Procedures:ELIMINATE IGNITION SOURCES,AVOID BREATHING VAPORS. DIKE AND ABSORB SPILL WITH INERT MATERIAL (SAND,SODA ASH,VERMICULITE,ETC) USING NON-SPARKING TOOLS,TRANSFER TO CONTAINERS FOR DISPOSAL. REMOVE SATURATED CLOTHING,WASH AFFECTED SKIN AREAS.

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE AT AMBIENT TEMPERATURES OUT OF DIRECT SUNLIGHT AND AWAY FROM SOURCES OF IGNITION. USE ADEQUATE VENTILATION.
Other Precautions:AVOID EYE/SKIN CONTACT & BREATHING OF VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN.

Ventilation:LOCAL EXHAUST WITH EXPLOSION PROOF MOTORS

Protective Gloves:IMPERVIOUS

Eye Protection:SPLASH PROOF GOGGLES.

Other Protective Equipment:IMPERVIOUS APRON & OVERSHOES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:214F/101C

Vapor Pres:29

Vapor Densi

ty:3.45

Spec Gravity:0.94

Solubility in Water:SLIGHT

Appearance and Odor:COLORLESS LIQUID

Percent Volatiles by Volume:94

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

REDUCING & OXIDIZING MATERIALS.

Stability Condition to Avoid:ELEVATED TEMP,IGNITION SOURCES

Hazardous Decomposition Products:ACRID FUMES,CO,CO*2

Conditions to Avoid Polymerization:ELEVATED TEMP.REDUCING & OXIDIZING MATERIALS.

===== Disposal Cons

iderations =====

Waste Disposal Methods:COMPLY WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advic

e to verify and
assume responsibility for the suitability of this information to their
particular situation.