View NSN Online: https://aerobasegroup.com/nsn/6850-00-585-6426

Product ID:TRACER TECH K 410C MSDS Date:01/01/1987 FSC:6850 NIIN:00-585-6426 MSDS Number: BFGSJ === Responsible Party === Company Name: URESCO ARDROX Address:16961 KNOTT AVE **City:LA MIRADA** State:CA ZIP:90638-6015 Country:US CAGE:EO423 === Contractor Identification === Company Name: BRENT AMERICA, INC. Addres s:16961 KNOTT AVE. Box:City:LA MIRADA State:CA ZIP:90638-6015 Country:US Phone:714-739-2821 CAGE:23373 Company Name: URESCO ARDROX CAGE:EO423

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III) CAS:71-55-6 RTECS #:KJ2975000 Fraction by Wt: 100% Other REC Limits:NONE RECOMMENDED OSHA PEL:350 PPM ACGIH TLV:350 PPM/450STEL;9394 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1

\_\_\_\_\_

Effects of Overexposure: CAUSES ANAESTHETIC EFFECTS. HEADACHES, NAUSEA.

First Aid:SKIN:WASH W.SOAP & H\*20. EYES:FLUSH W. H\*20. INGESTED:DON'T INDUCE VOMITING. INHALED:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF NEED. KEEP WARM & QUIET. REMOVE CONTAMINATED CLOTHING. NEVER GIVE ANYTHING BY MOUTH TO UNCONSCIOUS PERSON.

\_\_\_\_\_

Flash Point:NONE Lower Limits:UNK Upper Limits:UNK Extinguishing Media:CO\*2, FOAM, DRY CHEM. Fire Fighting Procedures:NONE Unusual Fire/Explosion Hazard:MAY PRODUCE TOXIC VAPORS IF PRODUCT INVOLVED IN FIRE.

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS. ELIM IGNITION SOURCES. STOP LEAK. H\*20 SPRAY COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT, SHOVEL INTO METAL DRUMS: LG SPILL: DI KE W COMMERCIAL

ABSORBENT, PUMP INTO COVERED DRUMS.

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS CLOSED. MAINTAIN STANDARD HYGIENE FOR CHEM HANDLING. Other Precautions:NONE KNOWN

======= Exposure Controls/Personal Protection ==========

Respiratory Protection:NONE SHOULD BE NEEDED Ventilation:MECH

ANICAL(GENERAL) RECOMMENDED,LOCAL EXHAUST IF NEEDED Protective Gloves:PVC/RUBBER Eye Protection:AS REQUIRED Supplemental Safety and Health MSDS DTD 4/83

HCC:T4 Boiling Pt:B.P. Text:165F Vapor Pres:100 Vapor Density:4.5 Spec Gravity:1.3 Solubility in Water:NEGLIGIBLE Appearance and Odor:COLORLESS LIQUID-CHARACTERISTIC ODOR. Percent Volatiles by Volume:100

St

ability Indicator/Materials to Avoid:YES WATER;BECAUSE WATER-SLOW HYDROLYSIS PRODUCES CORROSIVE ACIDS Stability Condition to Avoid:OPEN FLAMES WELDING ARCS Hazardous Decomposition Products:HYDROGEN CHLORID & PHOSGENE.

Waste Disposal Methods:CONTACT SUPPLIER OR NOTIFY AUTHORITIES FOR DISPOSAL PROCEDURES.REMOVE TO FUME HOOD. PACKAGE & DISPOSE IN ACCORDANCE WITH INTERNATIONAL,FEDERAL,STATE AND LOCAL REGULATIONS.

Disclai

mer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.