

DEVOE MARINE COATING CO -- FORMULA 84/47,ZINC CHROMATE PRIMER,TT-P-645 --
8010-00-593-5612

===== Product Identification =====

Product ID:FORMULA 84/47,ZINC CHROMATE PRIMER,TT-P-645

MSDS Date:01/01/1985

FSC:8010

NIIN:00-593-5612

MSDS Number: BFGWH

=== Responsible Party ===

Company Name:DEVOE MARINE COATING CO

Address:4000 DUPONT CIRCLE

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

CAGE:EO141

=== Contractor Identification ===

Company Name:DEVOE MARINE COATING CO.

Address:4000 DUPONT CIRCLE

Box:7600

City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Phone:502-897-9861

CAGE:EO141

Company Name:GROW GROUP INC DEVOE AND REYNOLDS CO DIV

Address:4000 DUPONT CIRCLE

Box:City:LOUISVILLE

State:KY

ZIP:40207-4802

Country:US

Phone:502-361-2536

CAGE:97758

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE

7555000
Fraction by Wt: 30%
OSHA PEL:100 PPM

Inged Name:METHYL ALCOHOL (METHANOL) (SARA III)
CAS:67-56-1
RTECS #:PC1400000
Fraction by Wt: 100F/37C (PMCC)
Extinguishing Media:CO*2,DRY CHEMICAL,FOAM
Fire Fighting Procedures:SELF-CONT BREATH APP,WATER FOG TO COOL EXPOSED
CONTAINERS
Unusual Fire/Explosion Hazard:DUE TO PRESSURE BUILD-UP,CLOSED
CONTAINERS EXPOSED TO HEAT MAY EXPLODE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL S
OURCES OF IGNITION,AVOID BREATHING
VAPORS,VENTILATE AREA. CONTAIN SPILLED MATERIAL AND REMOVE WITH
INERT ABSORBENT AND NON-SPARKING TOOLS. STORE IN CLOSED CONTAINER
UNTIL PROPERLY DISPOSED OF.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F/48C OR NEAR
FIRE OR OPEN FLAME. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED TO
COMPLY WITH OSHA 1910.106.
Other Precautions:CLOSE CONTAINERS AFTER USE. DO NOT
REUSE EMPTY
CONTAINERS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN.
Ventilation:GENERAL DILUTION/LOCAL EXHAUST WITH EXPLOSION PROOF MOTORS.
Protective Gloves:SOLVENT RESIST
Eye Protection:SOLVENT RESIST EYEWEAR
Other Protective Equipment:NORMAL PROTECTIVE CLOTHING
Supplemental Safety and Health
MFR ID CODE: FORMULA 84/47,MD-7731/MD-8440. PKG: 1 PT

===== Phy

sical/Chemical Properties =====

Boiling Pt:B.P. Text:150F/65C

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:54

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS;RUBBER SOFTENS

Hazardous Decomposition Products:CO,CO*2,OXIDES OF NITROGEN,AND
CHROMATE COMPOUNDS

===== Disposal Considerations =====

Waste Disposal Meth

ods:DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND

FEDERAL REGULATIONS. INCINERATE ONLY IN APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.