View NSN Online: https://aerobasegroup.com/nsn/8030-00-597-5367

THE LOCKREY CO. INC. -- LIQUI MOLY NV THREAD COMPOUND -- 8030-00-597-5367

Product ID:LIQUI MOLY NV THREAD COMPOUND MSDS Date:01/01/1985 FSC:8030 NIIN:00-597-5367 MSDS Number: BFGZD === Responsible Party === Company Name: THE LOCKREY CO. INC. Emergency Phone Num:609-665-4794 CAGE:KO338 === Contractor Identification === Company Name: LOCKREY CO LUBRICANTS DIVISION А ddress:CEDAR SHORES Box:City:SOUTHHAMPTON State:NY ZIP:11968 Country:US CAGE:98113 Company Name: THE LOCKREY CO. INC. CAGE:KO338

Ingred Name:ETHYLENE GLYCOL (SARA III) CAS:107-21-1 RTECS #:KW2975000 OSHA PEL:C 50 PPM ACGIH TLV:C 50 PPM,VAPOR; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Ingred Name:MOLYBDENUM DISULFIDE CAS:1317-33-5 RTECS #:QA4697000 OSHA PEL:10 MG/M3 TDUST (MO) ACGIH TLV:10 MG/M3 (MO); 8990

Hazards Identification ====================================
Effects of Overexposure:NONE
======================================
First Aid:EYES,SKIN- FLUSH W/ WATER FOR AT LEAST 15 MINUTES.
======================================
Flash Point:470F, 243.3,(OC) Extinguishing Media:CO*2, DRY CHEMICAL, FOAM Fire Fighting Procedures:SELF-CONTAIN BREATH APP Unusual Fire/Explosion Hazard:BURNING CAN PRODUCE OXIDES OF NITROGEN, SULFUR, & CO*2.
===== ================================
Spill Release Procedures:COLLECT FOR DISPOSAL
======================================
Handling and Storage Precautions:NONE Other Precautions:NONE
======================================
Respiratory Protection:MFR RECOMMENDS NONE Ventilation:LOCAL EXHAUST Protective Gloves:PLASTIC EXHAUST Eye Protection:SAFETY GLASSES Other Protective Equipment:EYE & SAFETY SHOWER Supplemen tal Safety and Health ====================================
HCC:N1 Boiling Pt:B.P. Text:482F, 250C Vapor Density:1 Spec Gravity:0.999 Evaporation Rate & amp; Reference:NEGLIGIBLE Solubility in Water:NEGLIGIBLE Appearance and Odor:BLUISH GRAY;SWEET,PLEASANT ODOR. Percent Volatiles by Volume:0
======================================

dition to Avoid:ABNORMAL CONDITIONS PRODUCE INSTABILITY. Hazardous Decomposition Products:BURNING CAN PRODUCE OXIDES OF NITROGEN, SULFUR, CO*2.

Waste Disposal Methods:MFR RECOMMENDS INCINERATION. WASTE DISPOSAL METHOD MUST BE IAW FEDERAL, STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The U

nited States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.