

DURON, INC. -- TT-E-508C -- 8010-00-597-8195

===== Product Identification =====

Product ID:TT-E-508C

MSDS Date:01/01/1985

FSC:8010

NIIN:00-597-8195

MSDS Number: BFHCL

=== Responsible Party ===

Company Name:DURON, INC.

Address:10406 TUCKER ST

City:BELTSVILLE

State:MD

ZIP:20705-2201

Country:US

CAGE:LO183

=== Contractor Identification ===

Company Name:DURON INC AMERICAN DIV

Address:10406 TUCKER ST

B

City:BELTSVILLE

State:MD

ZIP:20705-2201

Country:US

CAGE:55652

Company Name:DURON, INC.

Address:10406 TUCKER STREET

Box:City:BELTSVILLE

State:MD

ZIP:20705-4600

Country:US

Phone:301-937-4600

CAGE:LO183

===== Composition/Information on Ingredients =====

Ingred Name:TITANIUM DIOXIDES SILICATES CALCIUM CARBONATE

Fraction by Wt: 48.6%

Ingred Name:ALKYD RESIN (SOLIDS)

Fraction by Wt: 23.0%

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 28.1%

ACGIH

TLV:100 PPM

Ingred Name:DRIERS  
Fraction by Wt: 0.3%

=====  
Hazards Identification =====

Effects of Overexposure:IRRIT OF RESPIRATORY TRACT & EYES.INHAL. OF  
HIGH VAPOR CONCENTRATIONS MAY HAVE RESULTS RANGING FROM

=====  
First Aid Measures =====

First Aid:EYES-FLUSH W/WATER FOR 15 MIN-GET MEDICAL ATTN.IF OVERCOME BY  
VAPOR, REMOVE FROM EXPOSED AREA.IF BREATHING IS IRREGULAR OR  
STOPPED,START RESUSCITATION.

=====  
Fire Fighting Measures =====

Flash Point:104F TCC 40 C  
Lower Limits:0.9%  
Extinguishing Media:USE CARBON DIOXIDE,DRY CHEMICAL OR FOAM  
Fire Fighting Procedures:FIGHT LIKE A GASOLINE FLASH FIRE  
Unusual Fire/Explosion Hazard:EXPOSURE TO EXTREME HEAT MAY CAUSE  
BURSTING OF CLOSED CONTAINERS.

=====  
Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES,KEEP PEOPLE  
AWAY.RECOVER LIQ.,ADD ABSORBENT TO  
SPILL AREA.AVOID BREATHING  
VAPORS. VENTILATE ENCLOSED SPACES.KEEP PETROLEUM PRODUCTS OUT OF  
ALL PUBLIC SEWER & STREAM.

=====  
Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS,AND OPEN  
FLAME.  
Other Precautions:AVOID PROLONGED CONTACT W/SKIN. DO NOT TAKE  
INTERNALLY.

=====  
Exposure Controls/Personal Protection =====

Respiratory Protection:HYDROCARBON OR ORGANIC VAPOR CANISTERS.SELF  
CNTN

G APPARATUS ABOVE

Ventilation:LOC. EXHAUST-FACE 60 FPM

Protective Gloves:MUST COMPLY W/S

Eye Protection:SECTION 1910,132-.135 OSHA

Other Protective Equipment:STDS.

Supplemental Safety and Health

EFFECTS OF OVEREXPOSURE(CONTD)DIZZINESS AND HEADACHES TO UNCONSCIOUSNESS.

===== Physical/Chemical Properties =====

Vapor Density:HEAV

Spec Gravity:1.369

Appearance and Odor:LIQUID PAINT-MILD ODOR

Percent Volatiles by Volume:48.9

===== Stability and Reactivity

Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:STRONG OXIDANTS LIKE LIQ. CHLORINE & CONCENTRATED OXYGEN HIG

Hazardous Decomposition Products:CARBON MONOXIDE IN THE CASE OF COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods:PLACE IN CLOSED DOT APPRVD CONTAINER.RAGS & ABSORBENT MATERIAL SHD BE IMMED.IMMERSED IN WATER.USE APPROVED LANDFILL IN ACCORD. W/LOCAL STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular

ar situation.