

NORRIS PAINT & VARNISH CO.,INC -- TT-P-29J,ORANGE,32630,LATEX FLAT WALL PAINT --
8010-00-598-5727

=====
===== Product Identification =====

Product ID:TT-P-29J,ORANGE,32630,LATEX FLAT WALL PAINT

MSDS Date:01/01/1985

FSC:8010

NIIN:00-598-5727

MSDS Number: BFHHY

=== Responsible Party ===

Company Name:NORRIS PAINT & VARNISH CO.,INC

Emergency Phone Num:503-364-2277

CAGE:GO781

=== Contractor Identification =

==

Company Name:NORRIS PAINT & VARNISH CO

Box:2023

CAGE:GO781

Company Name:NORRIS PAINT CO., DIV WHITTAKER COATINGS

Address:1675 COMMERCIAL ST NE

Box:2023

City:SALEM

State:OR

ZIP:97308

Country:US

Phone:503-364-2277

CAGE:33148

=====
===== Composition/Information on Ingredients =====

Ingred Name:VINYL ACETATE (SARA III)

CAS:108-05-4

RTECS #:AK0875000

Fraction by Wt: 22.0%

OSHA PEL:10 PPM/15 STEL

ACGIH TLV:10 PPM/15,A3 STEL;93

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ET

HYLENE GLYCOL (SARA III)
CAS:107-21-1
RTECS #:KW2975000
Fraction by Wt: 2.0%
OSHA PEL:C 50 PPM
ACGIH TLV:C 50 PPM,VAPOR; 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:TITANIUM DIOXIDE
CAS:13463-67-7
RTECS #:XR2275000
Fraction by Wt: 9.7%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:ALUMINUM SILICATE (AS NUISANCE DUST OR PARTICULATES NOT
OTHERWISE REGULATED)
CAS:1302-76-7
RTECS #:BD1450000
Fraction by Wt: 30.3%
OSHA PEL:15 MG/M3 TOTAL DUST
ACGIH TLV:10 MG/M3 TDUS
T;8990

Ingred Name:PHENYLMERCURIC ACETATE (SARA III)
CAS:62-38-4
RTECS #:OV6475000
Fraction by Wt: 0.1%
OSHA PEL:0.1 MG HG/M3;CEIL;S
ACGIH TLV:0.01 MG HG/M3; 9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:NAUSEA WHEN INGESTED

=====
===== First Aid Measures =====

First Aid:INGESTION:INDUCE VOMITING,GET MEDICAL ATTENTION.

=====
===== Fire Fighting Measures =

=====

Flash Point:NONE

===== Accidental Release Measures =====

Spill Release Procedures:CLEAN UP WITH SOAP AND WATER.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT FREEZE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN.

Ventilation:GENERAL

Supplemental Safety and Health

ADD

ADDITIONAL INGREDIENTS:WATER,35.9%, COLORANTS, 1.0%; SURFACTANTS, 1.0%.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212F/100C

Vapor Pres:24

Spec Gravity:1.40

Evaporation Rate & Reference:1 (WATER)

Solubility in Water:COMPLETE

Percent Volatiles by Volume:64

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OIL AND OIL-BASE MATERIALS,PETROLEUM DISTILLATES

===== Disposal Considerations =====

Disposal Considerations =====

Waste Disposal Methods:FLUSH DOWN DRAIN

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assure

me responsibility for the suitability of this information to their particular situation.