View NSN Online: https://aerobasegroup.com/nsn/8010-00-598-5733

Product ID:WHITE #37875 MSDS Date:01/01/1987 FSC:8010 NIIN:00-598-5733 **MSDS Number: BFHJQ** === Responsible Party === Company Name: PPG INDUSTRIES, ONE GATEWAY CNTR, PITTSBURGH, PA Emergency Phone Num:412-434-3131 CAGE:LO671 === Contractor Identification === Company Name: PPG INDUSTRIES Α ddress:ONE GATEWAY CENTER Box:City:PITTSBURGH State:PA ZIP:15222-1416 Country:US CAGE:88944 Company Name: PPG INDUSTRIES, ONE GATEWAY CNTR, PITTSBURGH, PA CAGE:LO671

Ingred Name:ETHYLENE GLYCOL (SARA III) CAS:107-21-1 RTECS #:KW2975000 Fraction by Wt: 5.0% OSHA PEL:C 50 PPM ACGIH TLV:C 50 PPM,VAPOR; 9192 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB

Effects of Overexpos

ure:SKIN CONTACT:POSSIBLE PRIMARY IRRITATION. EYE CONTACT:PRIMARY IRRITATION

======================================
First Aid:SPLASH(EYES):FLUSH IMMEDIATELY WITH COPIOUS QUANTITIES OF RUNNING WATER FOR AT LEAST 15 MINUTES.TAKE TO A PHYSICAN FOR DEFINITIVE MEDICAL TREATMENT. SPLASH(SKIN) REMOVE WITH SOAP AND WATER.REMOVE CNTA MINATED CLOTHING.
======================================
Fire Fighting Procedures:WATER MAY B E USED TO COOL CLOSED CONTAINERS Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE OR BURST(DUE TO THE BUILD-UP OF PRESSURE)WHEN EXPOSED TO EXTREME HEAT
======================================
Spill Release Procedures:RETURN MATERIAL TO CONTAINER
======================================
Handling and Storage Precautions:PROTECT FROM FREEZING Other Precautions:DO NOT TAKE INTERNALLY.DO NOT FLAME CUT,BRAZE OR WELD WITHOUT
NIOSH APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.
======================================
Respiratory Protection:IN RESTRICTED VENTILATION AREA USE NIOSH APPROVED CHEMICAL MECH.FILT Ventilation:LOCAL EXHAUST, MECH:KEEP TLV OF HAZARDOUS MATERIAL BELOW TLV
Protective Gloves:REQUIRED Eye Protection:REQUIRED Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING. Supplemental Safety and Health

====== Physical/Che

HCC:N1 Boiling Pt:B.P. Text:212F Vapor Pres:17 Vapor Density:>1 Spec Gravity:1.44 Evaporation Rate & amp; Reference:SLOWER THAN ETHER Solubility in Water:YES 44% Appearance and Odor:OPAQUE LIQUID,MILD NON-OBJECTIONABLE ODOR Percent Volatiles by Volume:61.5

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:EXCESSIVELY HIGH STORAGE TEMPERATURES Hazardous Decomposition Pr oducts:MAY PRODUCE HAZARDOUS FUMES WHEN HEATED TO DECOMPOSITION

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE, AND FEDERAL REGULATIONS.DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, w

arrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.