

PRATT & LAMBERT - WICHITA DIV -- 742-324;TT-E-489, COMP L, CL A, YELLOW 13655 --  
8010-00-598-5945

=====  
Product Identification  
=====

Product ID:742-324;TT-E-489, COMP L, CL A, YELLOW 13655

MSDS Date:01/01/1987

FSC:8010

NIIN:00-598-5945

MSDS Number: BFHLR

=== Responsible Party ===

Company Name:PRATT & LAMBERT - WICHITA DIV

Emergency Phone Num:(316) 733-1361

CAGE:PRATT

=== Contractor Identification =

==

Company Name:PRATT & LAMBERT

Address:250 PETTIT AVE

Box:2153

City:BELLMORE

State:NY

ZIP:11710

Country:US

Phone:800-647-2253

CAGE:PRATT

=====  
Composition/Information on Ingredients  
=====

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR  
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05MG/M3(CR)A2;8990

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 T

DUST; 9293

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

=====  
===== Hazards Identification =====

Effects of Overexposure:INH: ANESTH, IRRIT OF RESP TRACT OR ACUTE CNS  
DEPRSSN W/HDACHE, DIZ, UNCON, COMA. SKIN/EYE IRRIT.

=====  
===== First Aid Measures =====

First Aid:CNTCT: FLUSH SKIN/EYES W/PLENTY WATER WHILE REMOVING CONTAM  
CLOTHING. INH: REMOVE TO FRESH AIR, CALL MD IF  
SYMPTOMS PERSIST.

=====  
===== Fire Fighting Measures =====

Flash Point:104F TCC

Lower Limits:1.1

Extinguishing Media:SM FIRES: CO\*2, DRY CHEM. LG FIRES: POLYMER FOAM  
PREFERRED.

Fire Fighting Procedures:USE SELF-CNTND BRTHNG APPARATUS

Unusual Fire/Explosion Hazard:CLOSED CNTNRS EXPOSED TO HEAT MAY EXPLODE  
DUE TO PRESS BUILD-UP.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID  
BRTHNG  
VAPORS. VENT AREA. REMOVE W/INERT ABSORBENT & NON-SPARKING TOOLS.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LG QTY  
BLDGS DESIGNED TO COMPLY W/OSHA 1910.106. DO NOT TAKE INTERN. ADD  
LABEL WARNING.

Other Precautions:GROUND CNTNRS WHEN POURING. AVOID FREE FALL OF LIQ IN  
EXCESS OF FEW IN. DO NOT FLAME CUT, BRAZE OR WELD COATED MATL W/O  
APPRVD RESP OR APPROPRIATE VENT. DOT: COMBUSTIB

LE.

=====  
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RESTRICT VENT: CHEM/MECH FLTR.

CLSD: AIR-LINE TYP E

Ventilation:GEN DILTN/LOCAL EXHST TO KEEP TLV/LEL BELOW LIMIT, REMV FUM

Protective Gloves:YES

Eye Protection:YES, FOR SPLASH

Other Protective Equipment:AVOID LONG EXPOSURE TO CONTAM CLOTHING

Supplemental Safety and Health

ADDRESS: 630 E. 13TH ANDOVER, KS 67002. THIS PRODUCT IS AN ENAMEL ALKYD

GLOSS. VAPOR PRESSURE BASED ON

MINERAL SPIRITS IS 3.2 VAPOR

DENSITY: HEAVIER THAN AIR. WT PER GAL: 99 LBS

=====  
===== Physical/Chemical Properties =====

HCC:F4

NRC/State Lic Num:NA

Boiling Pt:B.P. Text:311-373F

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:61.

=====  
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRES, HEAT & HOT SURFACES

=====  
===== Disposal Co

nsiderations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CNTNR. DISPOSE IAW FED,  
STATE, LOCAL REG.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek comp

etent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.