View NSN Online: https://aerobasegroup.com/nsn/8010-00-598-7211

PRATT AND LAMBERT INC -- ENAMEL ALKYD GLOSS FIRE RED 12199 -- 8010-00-598-7211

Product ID:ENAMEL ALKYD GLOSS FIRE RED 12199

MSDS Date:01/01/1987

FSC:8010

NIIN:00-598-7211

MSDS Number: BFHMP === Responsible Party ===

Company Name: PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153 City:WICHITA

State:KS ZIP:67201 Country:US

Info Phone Num:316-733-1361

Emergency

Phone Num:716-873-6000 DOT EMER 8002553924

CAGE:61196

=== Contractor Identification ===

Company Name: PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

======= Composition/Information on Ingredients ========

Ingred Name: MINERAL SPIRITS

CAS:64475-85-0 RTECS #:PY8240000 ACGIH TLV:100PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;919 2

EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS

Ingred Name: CADMIUM COMPOUNDS

RTECS #:EV0260000

ACGIH TLV:0.05MG/CUMTR

Ingred Name: CADMIUM SELENIDE SULFIDE

CAS:12626-36-7 RTECS #:EV2350000

ACGIH TLV:0.05MG/CUMTR

============= Hazards Identification ========================

Effects of Overexposure:PNEUMOCONIOSIS,PERMANENT NERVOUS SYSTEM DAMAGE,INTERNAL ORGAN DAMAGE.DELIBERATE INHALATION HARMFUL.

First Aid:INGESTION:

GET IMMEDIATE MEDICAL ATTENTION.INHALATION:REMOVE
TO FRESH AIR.RESTORE BREATHING.KEEP WARM AND QUIET.CONSULT
PHYSICIAN.EYES:15 MINUTE WATER FLUSH.CONSULT PHYSICIAN.SKIN:REMOVE
CONTAMINATED C LOTHING.WASH SKIN WITH SOAP AND WATER.

=========== Fire Fighting Measures ==========================

Flash Point:80F,27C

Extinguishing Media:CARBON DIOXIDE,DRY CHEMICALS,ALCOHOL,POLYMER FOAMS. Fire Fighting Procedures:SELF CONTAINED BREATHING APPAR.WATER-FOG TO COOL CONTAINERS.

Unusu

al Fire/Explosion Hazard:CONTAINER EXPLOSION HAZARD DUE TO EXTREME HEAT, EXPOSURE TO SOURCES OF IGNITION.

========= Accidental Release Measures =============

Spill Release Procedures:REMOVE SOURCES OF IGNITION.CONTAIN WITH INERT MATERIAL.TRANSFER TO COVERED METAL CONTAINERS.PREVENT ENTRY TO DRAINS,SEWERS AND GROUND WATER,WEAR RESPIRATORS,EYE,SKIN PROTECTION.REMOVE LIQUID WITH INER T ABSORBENT AND NON-SPARKING TOOLS.

====== Handling and Storag

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.CLOSE CONTAINER AFTER USE.DO NOT BREATHE FUMES,SANDING PARTICLES.

Other Precautions:DO NOT WELD, CUT OR BRAZE EMPTY CONTAINER. DO NOT CLEAN AND RE-USE CONTAINER. DO NOT USE PRESSURE TO EMPTY CONTAINER. GROUND AND BOND CONTAINER TO RECEIVING VESSEL.

====== Exposure Controls/Personal Protection ========

Ventilation:LOCAL VENTIL
ATION/EXHAUST TO REMOVE DECOMPOSITION
BYPRODUCTS
Protective Gloves:SOLVENT RESIST.

Eye Protection: FACE SHIELD; SHIELDED SPEC Supplemental Safety and Health

======== Physical/Chemical Properties ============

HCC:F3

Boiling Pt:B.P. Text:244F,118C

Vapor Density:>AIR

Evaporation Rate & Evaporation R

Percent Volatiles by Volume:62

======== Stability and Reactivity Data ==========

Stability Indicator/Materials to Avoid:YES STRONG ACIDS,ALKAL INES,OXIDIZERS. Stability Condition to Avoid:EXCESSIVE HEAT.SOURCES OF IGNITION.

Hazardous Decomposition Products:CO,CO*2,SMOKE FROM IGNITION

======= Disposal Considerations ============

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS.DISPOSE OF IN ACCORDANCE WITH EPA,LOCAL,STATE AND FEDERAL REGULATIONS FOR FLAMMABLE,HAZARDOUS WASTES.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by ele

ments of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.