

PRATT AND LAMBERT INC -- ENAMEL ALKYD GLOSS FIRE RED 12199 -- 8010-00-598-7211
===== Product Identification =====

Product ID:ENAMEL ALKYD GLOSS FIRE RED 12199

MSDS Date:01/01/1987

FSC:8010

NIIN:00-598-7211

MSDS Number: BFHMP

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency

Phone Num:716-873-6000 DOT EMER 8002553924

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

===== Composition/Information on Ingredients =====

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

ACGIH TLV:100PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;919

2

EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:CADMIUM COMPOUNDS
RTECS #:EV0260000
ACGIH TLV:0.05MG/CUMTR

Ingred Name:CADMIUM SELENIDE SULFIDE
CAS:12626-36-7
RTECS #:EV2350000
ACGIH TLV:0.05MG/CUMTR

===== Hazards Identification =====

Effects of Overexposure:PNEUMOCONIOSIS,PERMANENT NERVOUS SYSTEM
DAMAGE,INTERNAL ORGAN DAMAGE.DELIBERATE INHALATION HARMFUL.

===== First Aid Measures =====

First Aid:INGESTION:
GET IMMEDIATE MEDICAL ATTENTION.INHALATION:REMOVE
TO FRESH AIR.RESTORE BREATHING.KEEP WARM AND QUIET.CONSULT
PHYSICIAN.EYES:15 MINUTE WATER FLUSH.CONSULT PHYSICIAN.SKIN:REMOVE
CONTAMINATED C LOTHING.WASH SKIN WITH SOAP AND WATER.

===== Fire Fighting Measures =====

Flash Point:80F,27C
Extinguishing Media:CARBON DIOXIDE,DRY CHEMICALS,ALCOHOL,POLYMER FOAMS.
Fire Fighting Procedures:SELF CONTAINED BREATHING APPAR.WATER-FOG TO
COOL CONTAINERS.

Unusu
al Fire/Explosion Hazard:CONTAINER EXPLOSION HAZARD DUE TO EXTREME
HEAT,EXPOSURE TO SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION.CONTAIN WITH INERT
MATERIAL.TRANSFER TO COVERED METAL CONTAINERS.PREVENT ENTRY TO
DRAINS,SEWERS AND GROUND WATER,WEAR RESPIRATORS,EYE,SKIN
PROTECTION.REMOVE LIQUID WITH INER T ABSORBENT AND NON-SPARKING
TOOLS.

===== Handling and Storag

e =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.CLOSE CONTAINER AFTER USE.DO NOT BREATHE FUMES,SANDING PARTICLES.

Other Precautions:DO NOT WELD,CUT OR BRAZE EMPTY CONTAINER.DO NOT CLEAN AND RE-USE CONTAINER.DO NOT USE PRESSURE TO EMPTY CONTAINER.GROUND AND BOND CONTAINER TO RECEIVING VESSEL.

===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL VENTILATION/EXHAUST TO REMOVE DECOMPOSITION BYPRODUCTS

Protective Gloves:SOLVENT RESIST.

Eye Protection:FACE SHIELD;SHIELDED SPEC

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:244F,118C

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:62

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS,ALKAL

INES,OXIDIZERS.

Stability Condition to Avoid:EXCESSIVE HEAT.SOURCES OF IGNITION.

Hazardous Decomposition Products:CO,CO*2,SMOKE FROM IGNITION

===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS.DISPOSE OF IN ACCORDANCE WITH EPA,LOCAL,STATE AND FEDERAL REGULATIONS FOR FLAMMABLE,HAZARDOUS WASTES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by ele

ments of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.