

SEYMOUR OF SYCAMORE, INC. -- ALL PURPOSE PRIMER -- 8010-00-616-9181

===== Product Identification =====

Product ID:ALL PURPOSE PRIMER

MSDS Date:01/01/1987

FSC:8010

NIIN:00-616-9181

MSDS Number: BFJBW

=== Responsible Party ===

Company Name:SEYMOUR OF SYCAMORE, INC.

Address:917 CROSBY AVE

City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

CAGE:59581

=== Contractor Identification ===

Company Name:SEYMO

UR OF SYCAMORE

Address:917 CROSBY AVE.

Box:City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Phone:815-895-9101/800-255-3924

CAGE:59581

===== Composition/Information on Ingredients =====

Ingred Name:V M ' P NAPHTHA

Fraction by Wt: 4.6%

ACGIH TLV:500 PPM

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 31.3%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM; Z-2

ACGIH TLV:S, 50 PPM; 9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:METH

YL ISOBUTYL KETONE (HEXONE) (SARA III)

CAS:108-10-1

RTECS #:SA9275000

Fraction by Wt: 2.2%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:100 PPM

ACGIH TLV:50 PPM/75 STEL; 9394

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:PROPANE

Fraction by Wt: 14.6%

Ingred Name:ISOBUTANE

Fraction by Wt: 14.6%

=====  
===== Hazards Identification =====

Effects of Overexposure:IRRITATION TO LUNGS, SKIN, EYES. MAY CAUSE  
NERVOUS SYSTEM DEPRESSION

=====  
===== F  
First Aid Measures =====

First Aid:REMOVE FROM EXPOSURE, RESTORE BREATHING. FLUSH EYES WITH  
WATER FOR 15 MINUTES. WASH SKIN WITH SOAP AND WATER. REMOVE  
CONTAMINATED CLOTHING

=====  
===== Fire Fighting Measures =====

Flash Point:-10F,-23.3C

Lower Limits:1.2

Extinguishing Media:CO2, DRY CHEMICAL, FOAM

Fire Fighting Procedures:GOGGLES, SELF CONTAINED BREATHING APPARATUS

Unusual Fire/Explosion Hazard:HIGH HEAT MAY CAUSE CAN TO EXPLODE

=====  
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. VENTILATE AREA

=====  
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. EXPOSURE TO  
HEAT OR PROLONGED SUN EXPOSURE MAY CAUSE BURSTING.

Other Precautions:AVOID CONTINUOUS BREATHING OF VAPORS AND SPRAY MIST

=====  
===== Exposure Controls/Personal Protection =====

Ventilation:LOCAL OR MECHANICAL

## Supplemental Safety and Health

### ===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:NA

Vapor Density:>AIR

Evaporation Rate & Reference:>ETHER

Percent Volatiles by Volume:85

### ===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CARBON MONOXIDE

### ===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE. DIS  
POSE OF IN ACCORDANCE WTH  
GOVERNMENT REGULATIONS

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.