

SEYMOUR -- AEROSOL CLEANING SOLVENT, GP-00OT-0620 -- 7510-00-616-9588

=====
Product Identification
=====

Product ID:AEROSOL CLEANING SOLVENT, GP-00OT-0620

MSDS Date:01/01/1987

FSC:7510

NIIN:00-616-9588

MSDS Number: BFJDD

=== Responsible Party ===

Company Name:SEYMOUR/SYCAMORE, IL 60178

Emergency Phone Num:(815) 895-9101

CAGE:LO703

=== Contractor Identification ===

Company Name:SEYMOUR OF SYCAMORE

Address:917 CROSBY AVE.

Box:City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Phone:815-895-9101/800-255-3924

CAGE:59581

Company Name:SEYMOUR/SYCAMORE, IL 60178

CAGE:LO703

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ2975000

Fraction by Wt: 75%

OSHA PEL:350 PPM/450 STEL

ACGIH TLV:350 PPM/450STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ozone Depleting Chemical:1

Ingred Name:PRO

PANE
CAS:74-98-6
RTECS #:TX2275000
Fraction by Wt: 15%
OSHA PEL:1000 PPM
ACGIH TLV:ASPHYXIAN; 9192

Ingred Name:ISOBUTANE
CAS:75-28-5
RTECS #:TZ4300000
Fraction by Wt: 10%
ACGIH TLV:1000 PPM

===== Hazards Identification =====

Effects of Overexposure:DIZZINESS/NAUSEA/HEADACHE/LOSS OF
COORDINATION/EQUILBRIUM/UNCONSCIOUSNESS/EVEN DEATH.

===== First Aid Measures =====

First Aid:EYE CONTACT: IRRIGATE W/WATER FOR 5 MINUTE
S. SKIN CONTACT:
WASH OFF IN FLOWING WATER/SHOWER. REMOVE CONTAMINATED CLOTHING/WASH
BEFORE RE-USE. INHALATION: REMOVE TO FRESH AIR. IF DIFFICULT, GIVE
OXYGEN . INGESTION: DON'T INDUCE VOMITING. GETMED ATT.

===== Fire Fighting Measures =====

Flash Point:NONE
Lower Limits:1.90
Extinguishing Media:CO2, DRY CHEMICAL, FOAM
Fire Fighting Procedures:WATER TO COOL CONTAINERS TO PREVENT BURSTING.
WEAR SCBA.
Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT
MAY CAUSE BURSTING OF
AEROSOL CAN.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION, AVOID
BREATHING VAPORS, VENTILATE AREA. WIPE UP WITHNERT MATERIALS AND
PLACE IN APPROPRIATE CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:DON'T STORE ABOVE 120F. EXPOSURE TO
HEAT OR PROLONG EXPOSURE TO SUN MAY CAUSE BURSTING.
Other Precautions:USE ONLY

AS DIRECTED. INTENTIONAL MISUSE BY
DELIBERATELY CONCENTRATING VAPORS AND INHALING CONTENTS CAN BE
HARMFUL OR FATAL.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID CONTINOUS BREATHING OF VAPORS/SPRAY MIST.
SCBA >TLV LIMITS.

Ventilation:PROVIDE LOCAL EXHAUST VENTILATION TO KEEP BELOW TLV.

Protective Gloves:OPTIONAL

Eye Protection:GOGGLES

Supplemental Safety and Health

MSDS DATE: 06 OCT 1986.

===== Physical/Chemical Properties =====

HCC:V3

Vapor Density:>AIR

Evaporation Rate & Reference:FASTER THAN ETHER

Percent Volatiles by Volume:85%

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

METALLIC ALLUMINUM AND ZINC POWDERS.

Stability Condition to Avoid:DON'T STORE >120F. KEEP FROM SPARKS/PILOT
LIGHT/OPE N FLAME.

Hazardous Decomposition Products:FUMES MAY CONTAIN CO/OXIDES OF
NITROGEN AND PHOSGENE.

===== Disposal Considerations =====

Waste Disposal Methods:DON'T INCINERATE AEROSOL, DIPOSE OF IN
ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS. DON'T PLACE
AEROSOL CANS IN HOME COMPACTOR. DON'T PUNCTURE.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate

and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.