View NSN Online: https://aerobasegroup.com/nsn/7510-00-616-9588

Product ID:O-T-620C METHYL CHLOROFORM MSDS Date:12/01/1989 FSC:7510 NIIN:00-616-9588 MSDS Number: BFJDF === Responsible Party === Company Name: AMERICAN WRITING INK CO. INC. Address:33 ENDICOTT STREET City:NORWOOD State:MA ZIP:02062 Country:US Info Phone Num:617-762-0026 **Emergency Pho** ne Num:617-762-0026 Preparer's Name:H. GILMORE CAGE:82956 === Contractor Identification === Company Name: AMERICAN INK AND OIL CORP Address:33 ENDICOTT STREET Box:City:NORWOOD State:MA ZIP:02062-3006 Country:US Phone:781-762-0026 / FAX: 781-762-1617 CAGE:82956

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROEHANE) (SARA III) CAS:71-55-6 RTECS #:KJ2975000 Fraction by Wt: 96-98% Other REC Limits:NONE SPECIFIED OSHA PEL:350 PPM/45 0 STEL ACGIH TLV:350 PPM/450STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS Ozone Depleting Chemical:1

LD50 LC50 Mixture:ORAL LD50 (RAT) = 10300 MG/KG

Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic: CONTACT MAY CAUSE EYE IRRITATION WITH

TEMPORARY CORNEAL INJURY OR SKIN IRRITATION. MAY CAUSE RESPIRATORY TRACT IRRITATION, C

ENTRAL NERVOUS SYSTEM DEPRESSANT, LOSS OF

CONSCIOUSNESS AND EVEN DEATH CAN O CCUR AT HIGH LEVELS OF EXPOSURE. PROLONGED OR REPEATED EXPOSURE MAY CAUSE SKIN IRRITATION. MAY CAUSE DRYING OR FLAKING.

Explanation of Carcinogenicity:NOT LISTED AS A CARCINOGEN BY NTP, IARC OR OSHA

Effects of Overexposure:INCOORDINATION AND IMPAIRED JUDGMENT MAY OCCUR AT VAPOR EXPOSURES FROM 500-1000 PPM. DIZZINESS, DROWSINESS, AND GENERAL ANESTETHIC EFFECTS MAY OCCUR IN RANGES OF 1000 PPM AND

HIGHER.

Medical Cond Aggravated by Exposure:OVER EXPOSURE MAY CAUSE INCREASED SENSITIVITY TO ADRENALINE. OVER EXPOSURE WITH AN INSUFFICIENT SUPPLY OF OXYGEN MAY TEMPORARILY INCREASE CARDIAC IRRITABILITY. SYMTOMATIC AMINES MAY CAUSE ARRHYTHMIAS.

First Aid:INHALATION: REMOVE TO FRESH AIR. IF NOT BREATHING, RESUSCITATE. IF BREATHING IS DIFFICULT, GIVE OXYGEN. CALL A PHYSICIAN. EYE: FLUSH IMMEDIATELY WITH L

ARGE AMOUNTS OF WATER FOR

15 MINUTES. GET MEDICAL ATTENTION. SKIN: REMOVE CONTAMINATED CLOTHING. WASH WITH SOAP AND WATER PROMPTLY. INGESTION: DO NOT INDUCE VOMITING. GET IMMEDIATE MEDICAL ATTENTION. GIVE NOTHING BY MOUTH IF VICTIM IS UNCONSCIOUS.

Flash Point:NONE Lower Limits:7.5 Upper Limits:12.5 Extinguishing Media:USE WATER FOG Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA & FU LL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE. Unusual Fire/Explosion Hazard:VAPORS MAY DEVELOP A FLAMMABLE ATMOSPHERE IN CONFINED OR POORLY-VENTILATED AREAS. CONTENTS OF CANS UNDER PRESSURE. MAY BURST IN HEAT OF FIRE.

Spill Release Procedures:SMALL SPILL: WIPE UP WITH TOWELS OR MOP UP IMMEDIATELY. REMOVE TO OUT-OF-DOORS. LARGE SPILLS: WEAR NIOSH APPROVED RESPIRATOR. VENTILATE AREA. DIKE TO RETAIN FLUID. PUMP UP FREE LIQUID. RESIDUE WILL EV APORATE QUICKLY. DO NOT FLUSH TO SEWER/WATERWAY. Neutralizing Agent:NONE

 Handling and Storage Precautions:STORE IN A COOL, DRY, AREA AWAY FROM DIRECT SUNLIGHT. DO NOT PUNCTURE OR INCINERATE CAN. CONTROL CONCENTRATIONS BELOW THE EXPOSURE GUIDELINE.
Other Precautions:USE WITH ADEQUATE VENTILATION. LOCAL EXHAUST

VENTILATION MAY BE NECESSARY FOR SOME OPERATIONS. LETHAL CONCENTRATIONS ARE UNLIKELY BUT POSSIBLE WITH POOR VENTILATION AND VERY HIGH CONCENTRATIONS. KEEP FROM REACH OF CHILDREN.

======= Exposure Controls/Personal Protection ===============

Respiratory Protection: IN HIGH VAPOR AREA, USE NIOSH/MSHA APPROVED RESPIRATOR WITH ORGANIC VAPOR CARTRIDGE. USE SELF-CONTAINED BREATHING APPARATUS IF VAPOR LEVELS EXCEED 1000 PPM. Ventilation: LOCAL EXHAUST RECOMMENDED TO CONTROL VAPO RS BELOW 50% OF

TLV. USE MECHANICAL VENTILATION WHERE VAPORS MAY ACCUMULATE. Protective Gloves:NONE NORMALLY REQUIRED.

Eye Protection: USE CHEMICAL SAFETY GOGGLES.

Other Protective Equipment: APRON AND WORK CLOTHING TO MINIMIZE EXPOSURE.

Work Hygienic Practices:WASH THOROUGHLY AFTER USE AND BEFORE EATING, SMOKING OR USING TOILET FACILITIES. DO NOT BREATH VAPORS OR MIST. Supplemental Safety and Health

TARGET ORGANS ARE SKIN, CNS, CVS, AND EYES. BE SURE SPRAY POINT IS AWAY FROM FACE AND BODY. REPLACE VALVE CAP AFTER USE.

HCC:V2 Boiling Pt:B.P. Text:165F,74C Melt/Freeze Pt:M.P/F.P Text:-23F,-31C Decomp Temp:Decomp Text:>130F,>54C Vapor Pres:100 Vapor Density:4.55 Spec Gravity:1.321 Evaporation Rate & amp; Reference:6.0 (N-BUTYL ACETATE=1) Solubility in Water:NEGLIGIBLE Appearance and Odor:CLEAR, COLORLESS LIQUID. MILD, CHLOROFORM-LIKE ODOR.

Percent Volatiles by Volume:100

====== Stability

Stability Indicator/Materials to Avoid:YES

PROLONGED CONTACT WITH ALUMINUM AND RELATED ALLOYS. THIS CAN FORM HYDROCHLORIC ACID GAS.

Stability Condition to Avoid:HIGH TEMPERATURES, SPARKS, OPEN FLAMES AND WELDING ARCS WHICH INDUCE THERMAL DECOMPOSITION.

Hazardous Decomposition Products: WHEN INVOLVED IN FIRE,

1,1,1-TRICHLOROETHANE EMITS HIGHLY TOXIC AND IRRITATING HYDROGEN CHLORIDE AND PHOSGENE FUMES.

====== Disposal Considera

Waste Disposal Methods:DISPOSE OF I/A/W FEDERAL, STATE & LOCAL REGULATIONS. PREFERRED OPTION IS TO SEND TO LICENSED RECLAIMER. DO NOT PUNCTURE OR INCINERATE CAN.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liabili

ty for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.