

AMERICAN GAS AND CHEMICAL COMPANY,LTD -- LEAK-TEC 16-OX -- 6850-00-621-1820

===== Product Identification =====

Product ID:LEAK-TEC 16-OX

MSDS Date:05/18/1989

FSC:6850

NIIN:00-621-1820

MSDS Number: BFJJK

=== Responsible Party ===

Company Name:AMERICAN GAS AND CHEMICAL COMPANY,LTD

Address:220 PEGASUS AVENUE,

City:NORTHVALE

State:NJ

ZIP:07647-1904

Country:US

Info Phone Num:201-767-7300

Emergency Pho

ne Num:201-767-7300

Preparer's Name:GEORGE KOSEL

CAGE:03530

=== Contractor Identification ===

Company Name:AMERICAN GAS AND CHEMICAL COMPANY,LTD

Address:220 PEGASUS AVENUE,

City:NORTHVALE

State:NJ

ZIP:07647-1904

Country:US

Phone:201-767-7300

CAGE:03530

===== Composition/Information on Ingredients =====

Ingred Name:THE MANUFACTURER STATES THAT NO HAZARDOUS INGREDIENTS ARE
PRESENT IN THIS PRODUCT.

RTECS #:9999999ZZ

Other REC Limits:NONE SPECIFIED

Ingred Name:WATER

CAS:7732

=====
Hazards Identification
=====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-EYES:MILD IRRITATION. SKIN:MILD
IRRITATION. INHALATION:NOT CONSIDERED LIKELY. INGESTION:IRRITATION.
CHRONIC-EYES:IRRITATION. SKIN:IRRITATION. INHALATION:NOT CONSIDERED
LIKELY. INGESTION:IRRITATION.
Explanation of Carcinogenicity:NOT CONSIDERED TO
BE A CARCINOGEN BY
NTP, IARC, OR OSHA.
Effects of Overexposure:EYES:IRRITATION. SKIN:IRRITATION.
INHALATION:NOT CONSIDERED LIKELY. INGESTION:IRRITATION.
Medical Cond Aggravated by Exposure:NONE

=====
First Aid Measures
=====

First Aid:EYES:FLUSH WITH WATER. SEEK MEDICAL ATTENTION IF IRRITATION
PERSISTS. SKIN:WASH WITH SOAP AND WATER. INHALATION:NOT CONSIDERED
LIKELY. INGESTION:INDUCE VOMITING AND CALL A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:NONE
Lower Limits:NONE
Upper Limits:NONE
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM, OR DRY
CHEMICAL.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:NONE SPECIFIED BY MANUFACTURER.

=====
Accidental Release Measures
=====

Spill Release Procedures:ABSORB LIQUID WITH AN INERT ABSORBENT MATERIAL
AND PLACE IN AN APPROVED CONTAINER. FLUSH WITH WATER TO SANITARY
SEWER SYSTEM.
Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

=====
Handling and Storage
=====

Handling and Storage Precautions:CONSIDERED RELATIVELY TOXIC TO AQUATIC
LIFE AT CONCENTRATIONS AS LOW AS 0.1%. STRONG FOAMER.
Other Precautions:STORE IN A COOL, DRY AREA. KEEP CONTAINERS CLOSED.

=====
Ex

posure Controls/Personal Protection =====

Respiratory Protection:NONE SPECIFIED BY MANUFACTURER.

Ventilation:LOCAL MECHANICAL EXHAUST.

Protective Gloves:NON-ABSORBENT GLOVES.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:NONE

Work Hygienic Practices:WASH HANDS AFTER CONTACT WITH THIS MATERIAL. DO

NOT EAT, DRINK, OR SMOKE NEAR THIS MATERIAL.

Supplemental Safety and Health

BIODEGRADABILITY IS 90% OR BETTER AS DETERMINED BY THE SEMI-CONTINUOUS

ACTIVATED SLUDGE METHOD.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:212F,100C

Vapor Pres:17.5

Vapor Density:>1

Spec Gravity:1.01

pH:6-7.5

Evaporation Rate & Reference: