

ALCAN-TOYO AMERICA,INC.(OLD NAME:ALCAN ALUMINUM CO -- ATOMIZED ALUMINUM POWDER,ALCAN 101 OR 105 -- 6810-00-628-3385

===== Product Identification =====

Product ID:ATOMIZED ALUMINUM POWDER,ALCAN 101 OR 105

MSDS Date:09/01/1986

FSC:6810

NIIN:00-628-3385

MSDS Number: BFJMF

=== Responsible Party ===

Company Name:ALCAN-TOYO AMERICA,INC.(OLD NAME:ALCAN ALUMINUM CO

Address:CATON FARM ROAD AND ROUTE 53

Bo

x:920

City:JOLIET

State:IL

ZIP:60434

Country:US

Emergency Phone Num:(815) 727-5555

CAGE:76424

=== Contractor Identification ===

Company Name:ALCAN-TOYO AMERICA INC AFFIL OF ALCON ALUMINUM CORP

Address:1717 N NAPER BLVD SUITE 201

Box:City:NAPERVILLE

State:IL

ZIP:60540

Country:US

Phone:708-505-2160

CAGE:76424

===== Composition/Information on Ingredients =====

Ingred Name:ALUMINUM (SARA III)

CAS:7429-90-5

RTECS #:BD0330000

Fraction by Wt: 100.0%

OSHA PEL:15MG/M3 DUST/5 FUME

ACG

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:DUST MAY CAUSE RESPIRATORY TRACT IRRITATION.

Effects of Overexposure:INHALATION:HIGH CONCENTRATION CAN CAUSE RESPIRATORY TRACT IRRITATION;EYES:DUST MAY CAUSE IRRITATION;SKIN:REPEATED AND PROLONGED CONTACT MAY CAUSE SLIGHT IRRITATION;INGESTION:NEGLIGIBLE EFFECTS.

Medical Cond Aggravated by Exposure:PRE-EXISTING UPPER RESPIRATORY AND LUNG DISEASE SUCH AS,BUT NOT LIMITED TO,BRONCHITIS,EMPHYSEMA AND ASTHMA.

=====
===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

=====
===== Fire Fighting Measures =====

Flash Point:NONE
Extinguishing Media:USE CLASS "D" DRY CHEMICAL EXTINGUISHING AGENTS SUCH AS DRY SAND; DO NOT USE WATER OF HALOGENATED AGENT AS EXTINGUISHER.
Fire Fighting Procedures:USE SELF-CONTAINED BREATHING APPARATUS IN PRESSURE DEMAND MODE;GENTLY COVER THE BURNING POWDER WITH EXTINGUISHER(DO NOT MIX WITH POWDER).PREVENT DUST FORMATION.
Unusual Fire/Explosion Hazard:WATER & BURNING ALUMINUM POWDER REACT VIOLENTLY FORMING HYDROGEN & ALUMINUM OXIDE.ALUMINUM DUST MAY BE IGNITED BY STATIC DISCHARGE.DUST IN AIR MAY BE EXPLOSION.

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL IGNITION SOURCES.USE NON-SPARKING TOOLS(SHOVELS).WEAR APPROPRIATE PROTECTIVE EQUIPMENTS.TRANSFER SPILLED MATERIAL TO A LEAK PROOF CONTAINER FOR HAZARDOUS WASTE DISPOSAL.IF VACUUM CLEANER IS USED,IT SHOULD BE GROUNDED TO PREVENT STATIC.

=====
===== Handling and Storage =====

ge =====

Handling and Storage Precautions:USE NON-SPARKING HANDLING EQUIPMENT.COVER AND RESEAL PARTIALLY EMPTY CONTAINERS.KEEP COMPLETELY DRY.STORAGE AREA MUST BE OF FIRE RESISTANT CONSTRUCTN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE SUPPLIED AIR RESPIRATORY PROTECTION IN CONFINED OR ENCLOSED SPACES IF NEEDED.

Ventilation:LOCAL EXHAUST,EXPLOSION PROOF,MINIMUM FACE VELOCITY 60 FPM.NO SMOKING OR OPEN LIGHT I N WORK AREA.

Protective Gloves:USE CHEMICAL RESISTANT GLOVES & APRON

Eye Protection:CHEMICAL GOGGLES OR FACE SPLASH SHIELD

Supplemental Safety and Health

MFR STATED THAT THE POWDER IS ATOMIZED & UNCOATED,SPHERICAL OR IRREGULAR SHAPE;THE MSDS SHOWING "X" BEFORE THE P/N IS STRICTLY FOR SPHERICAL POWDER COVERED BY MIL-A-23950 & MIL-A-82728.THE MSDS SHOWIN G STRAIGHT NO IS FOR IRREGULAR SHAPED PARTICLES POWDER FOR MIL-A-512;THIS ENTRY IS FOR P/N:ALCAN 101;REF:DGSC-SLM 87252H

=====

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:4472F/2467C

Melt/Freeze Pt:M.P/F.P Text:1220F/660C

Spec Gravity:2.70

Solubility in Water:NEGLIGIBLE

Appearance and Odor:DULL GRAY TO METALLIC SILVER APPEARANCE,NO ODOR

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

WATER,HALOGENATED HYDROCARBONS,MINERAL ACIDS,ALKALIS AND STRONG OXIDIZING MATERIALS.

Stability Condition to Avoid:IMPROPER S

TORAGE WHICH WOULD ALLOW

INTRODUCTION OF WATER/MOISTURE,HEAT,SPARKS & FOREIGN MATERIAL.

Hazardous Decomposition Products:ALUMINUM WHEN REACTS WITH WATER,ACIDS OR ALKALIS,IT FORMS COMBUSTIBLE HYDROGEN GAS.

===== Disposal Considerations =====

Waste Disposal Methods:FOR DISPOSAL OF THIS MATERIAL AS A WASTE,ACT IN ACCORDANCE WITH ALL APPLICABLE FEDERAL,STATE & LOCAL WASTE MANAGEMENT REGULATIONS.MFR RECOMMENDS TO DISPOSE IN APPROVED HAZARDOUS WAST

E LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.