

AMERON INDUSTRIAL COATINGS DIVISION -- GRAY #36081 -- 8010-00-634-6703  
===== Product Identification =====

Product ID:GRAY #36081  
MSDS Date:01/01/1985  
FSC:8010  
NIIN:00-634-6703  
MSDS Number: BFJPR  
=== Responsible Party ===  
Company Name:AMERON INDUSTRIAL COATINGS DIVISION  
Address:201 N BERRY ST  
City:BREA  
State:CA  
ZIP:92621-3904  
Country:US  
Info Phone Num:714-529-4597  
Emergency Phone Num:714-529-4597  
CAGE:09869  
=== Contractor Identification ===  
Company Name:AMERON INDUSTRIAL COATINGS DIVISION  
Address:201 N BERRY ST  
Box:City:BREA  
State:CA  
ZIP:92621-3904  
Country:US  
Phone:714-529-4597  
CAGE:09869

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)  
CAS:8030-30-6  
RTECS #:SE7555000  
Fraction by Wt: 39.0%  
OSHA PEL:100 PPM

===== Hazards Identification =====

Effects of Overexposure:ANESTHETIC, IRR.

OF RESPIRATORY TRACT OR ACUTE  
NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

===== First Aid Measures =====

First Aid:IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE  
CONTAMINATED CLOTHING. IF INHALED REMOVE TO FRESH AIR. CALL A  
PHYSICAN IF CONDITIONS PERSIST.

===== Fire Fighting Measures =====

Flash Point:86F TCC  
Lower Limits:1.1  
Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE

FIRES-FOAM

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID  
BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING  
TOOLS

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 12  
0F. STORE LARGE  
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE  
FLAMMABLES.  
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID  
FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR  
SUPPLIED RESPIRATOR  
Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY  
Supplemental Safety and Health  
RESPIRATOR USE BASED ON

# CHEM CONC. AND CONDITION OF USE

## ===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:311-373F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:61.0

## ===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRE,HEAT AND HOT SURFACES

## ===== Disposal Considerations =====

Waste Disposal

Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND  
FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.