

THE AKRON PAINT & VARNISH CO. -- LR-7130B-DARK GULL GRAY W W TYPE II #356231 --
5610-00-641-0426

=====
===== Product Identification =====

Product ID:LR-7130B-DARK GULL GRAY W W TYPE II #356231

MSDS Date:01/01/1987

FSC:5610

NIIN:00-641-0426

MSDS Number: BFJSD

=== Responsible Party ===

Company Name:THE AKRON PAINT & VARNISH CO.

Address:1390 FIRESTONE PARKWAY

City:AKRON

State:OH

ZIP:44301-1624

Country:US

CAGE:KO225

=== Contractor Identification ===

Company Name:AKRON PAINT AND VARNISH INC

Address:1390 FIRESTONE PARKWAY

City:AKRON

State:OH

ZIP:44301-1624

Country:US

Phone:216-773-8911

CAGE:70228

Company Name:THE AKRON PAINT & VARNISH CO.

Address:1390 FIRESTONE PARKWAY

Box:City:AKRON

State:OH

ZIP:44301-1624

Country:US

CAGE:KO225

=====
===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 39.

6%
OSHA PEL:100 PPM

Ingred Name:N-BUTYL ACETATE (SARA III)
CAS:123-86-4
RTECS #:AF7350000
Fraction by Wt: 2.2%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:150 PPM
ACGIH TLV:150 PPM/200STEL;9394
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
Fraction by Wt: 5.4%
Other REC Limits:NONE RECOMMENDED
OSHA PEL:200 PPM; Z-2
ACGIH TLV:S, 50 PPM; 9394
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:MINERAL SPIRITS
CAS:64475-85-0
RTECS #:PY
8240000
Fraction by Wt: 0.4%
ACGIH TLV:500PPM

Ingred Name:BUTYRALDEHYDE OXIME
CAS:110-69-0
RTECS #:ES3500000
Fraction by Wt: 0.5%

===== Hazards Identification =====

Effects of Overexposure:PROLONGED OR REPEATED EXPOSURE MAY CAUSE
NAUSEA,HEADACHE AND LOSS CONSCIOUSNESS;NARCOSSIS & IRRITATI

===== First Aid Measures =====

First Aid:SKIN CONTACT:WASH CAREFULLY W/MINERAL SPIRITS,THEN W/SOAP &
WATER.EYE CONTACT:FLUSH

PROMPTLY & THOROUGHLY W/WATER & OBTAIN
MEDICAL ATTENTION. INHALATION: REMOVE INDIVIDUAL TO FRESH AIR & USE
OXYGEN IF NECESSARY. "OBTAIN MEDICAL ATTENTION"

===== Fire Fighting Measures =====

Flash Point: 40F CC TOL. 4C
Extinguishing Media: CARBON DIOXIDE, FOAM OR DRY CHEMICAL.
Fire Fighting Procedures: WATER SPRAY TO COOL CONTAINERS, WEAR
SELF-CONTAINED BREATHING
Unusual Fire/Explosion Hazard: HEAT MAY CAUSE DISRUPTIVE PRESSURE OF
CONTAINERS & FLAMMABLE
VAPORS MAY FORM EXPLOSIVE MIXTURE W/AIR

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. DAM-UP TO LIMIT
SPREADING. ABSORB ON INERT MATERIAL. VENTILATE AREA.

===== Handling and Storage =====

Handling and Storage Precautions: DO NOT DROP CONTAINERS. AVOID HEAT,
SPARKS & OPEN FLAME. STORE AT ROOM TEMPERATURE W/GOOD VENTILATION.
Other Precautions: DO NOT TAKE INTERNALLY. AVOID PROLONGED
INHALATION &
BODY CONTACT GROUND CONTAINER WHILE POURING. CONSULT NFPA CODE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE APPRO. BUR. OF MINES APPRV'D RESPIRATOR WHEN
SPRAYING OR APPLYING
Ventilation: PROVIDE ADEQUATE VENTILATION & EXPLOSION-PROOF EQUIPMENT.
Protective Gloves: CHEMICAL RESIST
Eye Protection: SAFETY GOGGLES W/SIDE SHIELD
Other Protective Equipment: NORMAL PROTECTIVE CLOTHING
Supplemental Safety and Health
BOILING RANGE: I.B.P.
: 231F (TULUOL) 111C

===== Physical/Chemical Properties =====

HCC: F3
Boiling Pt: B.P. Text: I.B.P. 231F
Vapor Density: HEAVY
Evaporation Rate & Reference: SLOWER THAN ETHER
Percent Volatiles by Volume: 68.6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
AVOID OXIDIZING AGENTS.
Hazardous Decomposition Products: COMBUSTION IN RESTRICTED ENVIRONMENT
CAN PROD. CARBON MONOXIDE
Conditions to Avoid Polymerization

n:STORAGE OF WETTED COMBUSTIBLE
MATERIALS MAY CAUSE SPONTANEOUS

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE W/APPLICABLE POLLUTION
CONTROL REGULATIONS. DO NOT INCINERATE CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants
this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.