View NSN Online: https://aerobasegroup.com/nsn/8010-00-641-0429

THE AKRON PAINT & VARNISH CO -- LR-7356D BLACK W W TYPE I #37038 -- 5610-00-641-0429

Product ID:LR-7356D BLACK W W TYPE I #37038

MSDS Date:01/01/1987

FSC:5610

NIIN:00-641-0429

MSDS Number: BFJSH === Responsible Party ===

Company Name: THE AKRON PAINT & VARNISH CO

Address: 1390 FIRESTONE PARKWAY

City:AKRON State:OH

ZIP:44301-1624 Country:US CAGE:KO225

=== Contracto

r Identification ===

Company Name: AKRON PAINT AND VARNISH INC

Address:1390 FIRESTONE PARKWAY

City:AKRON State:OH

ZIP:44301-1624

Country:US

Phone:216-773-8911

CAGE:70228

Company Name: THE AKRON PAINT & VARNISH CO.

Address:1390 FIRESTONE PARKWAY

Box:City:AKRON

State:OH

ZIP:44301-1624 Country:US CAGE:KO225

======= Composition/Information on Ingredients ========

Ingred Name: N-BUTYL ACETATE (SARA III)

CAS:123-86-4

RTECS #:AF7350000 Fraction by Wt: 0.7%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:150 PPM

ACGIH TLV:150 PPM/200STEL;9394

EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS

Ingred Name: NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000 Fraction by Wt: 27.5% OSHA PEL:100 PPM

Ingred Name: MINERAL SPIRITS

CAS:64475-85-0 RTECS #:PY8240000 Fraction by Wt: 7.4% ACGIH TLV:500PPM

Ingred Name: TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000 Fraction by Wt: 2.3%

Other REC Limits: NONE RECOMMENDED

OSHA PEL:200 PPM; Z-2 ACGIH TLV:S, 50 PPM; 9394 EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name: BUTYRALDEHYDE OXIME

CAS:110-69-0

RTECS #:ES3500000 Fraction by Wt: 0.5%

========= Hazards Identification ===============

Effects of Overexposure:PROLONGED OR REPEATED EXPOSURE MAY CAUSE NAUSEA, HEADACHE, HEADACHE & LOS OF CONSCIOUSNESS; NARCOSSIS

First Aid:SKIN CONTACT:WASH CAREFULLY W/MINERAL SPIRITS,THEN W/SOAP & WATER EYE CONTACT:FLUSH PROMPTLY &THROUGHLY W/WATE

| OXYGEN IF NEC ESSARY.OBTAIN MEDICAL ATTENTION. |
|---|
| ====================================== |
| Flash Point:40F CC TO 4C Extinguishing Media:CARBON DIOXIDE,FOAM OR DRY CHEMICAL. Fire Fighting Procedures:WATER SPRAY TO COOL CONTAINERS.WEAR SELF-CONTAINED BREATHING Unusual Fire/Explosion Hazard:HEAT MAY CAUSE DISRUPTIVE PRESSURE OF CONTAINERS,& FLAMMABLE VAPORS MAY FORM EXPLOSIVE MIXT URE W/AIR |
| ========= Accidental Release Measures ========== |
| Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. DAM-UP TO LIMIT SPREADING |
| ====================================== |
| Handling and Storage Precautions:DO NOT DROP CONTAINERS.AVOID HEAT,SPARKS & OPEN FLAME. STORE AT ROOM TEMPERATURE W/GOOD VENTILATION. Other Precautions:DO NOT TAKE INTERNALLY.AVOID PROLONGED INHALATION & BODY CONTACT.GROUND CONTAINER WHILE POURING.CON SULT NFPA CODE. |
| ====== Exposure Controls/Personal Protection ======== |
| Respiratory Protection:USE APPROP. BUR. OF MINES APPRVD RESPIRATOR WHEN SPRAYING OR APPLYIN Ventilation:PROVIDE ADEQUATE VENTILATION & EXPLOSION-PROOF EQUIPMENT. Protective Gloves:CHEMICAL RESIST Eye Protection:SAFETY GOGGLES W/SIDE SHI Other Protective Equipment:NORMAL PROTECTIVE CLOTHING Supplemental Safety and Health BOILING RANGE:I.B.P:231F(TOLUOL) 111C |
| ======== Physical/Chemical Properties |

MEDICAL ATTENTION.INHALATION:REMOVE INDIVIDUAL TO FRESH AIR & USE

R & OBTAIN

HCC:F3
Boiling Pt:B.P. Text:I.B.P:231F
Vapor Density:HEAV
Evaporation Pate & amp: Pefer

Evaporation Rate & Evaporation R

Percent Volatiles by Volume:58.2

======== Stability and Reactivity Data =========

Stability Indicator/Materials to Avoid:YES
AVOID OXIDIZING AGENTS.
Hazardous Decomposition Products:COMBUSTION IN RESTRICTED ENVIRONMENT
CAN PRODUCE CARBON MONO

======= Disposal Considerations ===========

Waste Disposal Methods:DISPOSE I N ACCORDANCE W/APPLICABLE POLLUTION CONTROL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.