

SUNNYSIDE CORPORATION -- ISOPROPYL ALCOHOL;CODE:832 -- 6505-00-655-8366

=====  
Product Identification  
=====

Product ID:ISOPROPYL ALCOHOL;CODE:832

MSDS Date:01/01/1987

FSC:6505

NIIN:00-655-8366

MSDS Number: BFJZB

=== Responsible Party ===

Company Name:SUNNYSIDE CORPORATION

Address:225 CARPENTER AVE

City:WHEELING

State:IL

ZIP:60090-6009

Country:US

Emergency Phone Num:708-541-5700

CAGE:9J570

=== Contra

ctor Identification ===

Company Name:BERKMANN MFG CO

Box:City:CHICAGO

State:IL

ZIP:60600

CAGE:95570

Company Name:SUNNYSIDE CORP

Address:225 CARPENTER AVE

Box:City:WHEELING

State:IL

ZIP:60090-6009

Country:US

Phone:847-541-5700

CAGE:9J570

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 100%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

=====  
Hazards Identifica

tion =====

Effects of Overexposure:MAY IRRITATE MUCOUS MEMBRANE IRRITATION & NARCOTIC EFFECTS;PROLONGED SKIN CONTACT MAY BE ABSORPTION.

===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H\*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =  
=====

Flash Point:55F/12.8C (T.C.C

Lower Limits:2.3

Extinguishing Media:CO\*2,FOAM,DRY CHEMICAL,WATER SPRAY;DO NOT USE DIRECT WATER.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA IN CONFINED AREA.COOL CONTR/H\*2

Unusual Fire/Explosion Hazard:DO NOT STORE OR MIX WITH STRONG OXIDANTS;

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;REMOVE ALL IGNITION SOURCES.DIKE LARGE SPILL & CONTAIN;F

OR SMALL SPILL USE

SUITABL ABSORBENT MATERIAL AND RECOVER-PROPER DISPOSAL

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY AND WELL VENTILATED AREA;KEEP AWAY FROM HEAT,OPEN FLAMES;KEEP CONTAINER CLOSED WHEN NOT IN USE.

Other Precautions:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE VAPORS;WASH THOROUGHLY AFTER EACH USE.

===== Exposure Controls/Personal Protection =====

Ventilation:PROVIDE

MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN 1.0

Spec Gravity:0.78

Evaporation Rate & Reference: