

EXXON COMPANY,USA. -- 1982 ATF (HYDRAULIC FLUID) -- 9150-00-657-4959

===== Product Identification =====

Product ID:1982 ATF (HYDRAULIC FLUID)

MSDS Date:04/16/1979

FSC:9150

NIIN:00-657-4959

MSDS Number: BFKCY

=== Responsible Party ===

Company Name:EXXON COMPANY,USA.

Box:2180

City:HOUSTON

State:TX

ZIP:77001

Country:US

Info Phone Num:713-656-2443

Emergency Phone Num:713-656-3424

CAGE:2F871

=== Contr

actor Identification ===

Company Name:EXXON COMPANY U.S.A.

Box:2180

City:HOUSTON

State:TX

ZIP:77252-2180

Country:US

Phone:713-656-5949 / 713-656-3424

CAGE:29700

Company Name:EXXON COMPANY,USA

Address:1251 AVE OF THE AMERICAS

Box:2180

City:NEW YORK

State:NY

ZIP:10020-1104

Country:US

CAGE:2F871

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

===== Composition/Information on Ingredients =====

Ingred Name:COMPLEX MIXTURE OF PETROLEUM HYDROCARBONS.

Other REC Limits:5MG/CUM,OIL MIST

Ingred Name:SELECTED ADDITIVES

===== Hazards Identification =====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Health Hazards Acute and Chronic:ACUTE:MILID SKIN IRRITATATION ON CONTACT CHRONIC:NOT KNOWN

Explanation of Carcinogenicity:N/R.

Effects of Overexposure:PROLONGED OR REPEATED SKIN CONTACT MAY CAUSE MILD SKIN IRRITATION.

===== = First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point Method:COC

Flash Point:380F/193C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:FOAM,DRY CHEMICAL,CO*2,WATER-FOG OR SPRAY

Fire Fighting Proc

edures:USE NIOSH/MASHA APPROVED SCBA IN AN ENCLOSED AREA.COOL EXPOSED CONTAINERS WITH WATER SPRAY.AVOID BREATHING VAPORS OR FUMES.

Unusual Fire/Explosion Hazard:DO NOT MIX OR STORE WITH STRONG OXIDANTS LIKE LIQUID CHLORINE OR CONC.OXYGEN

===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;USE SUITABLE ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL.

===== Handling and Storage =====

=====

Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED AREA.AVOID HEAT,OPEN FLAMES.KEEP CONTAINER CLOSED WHEN NOT IN USE.
Other Precautions:DO NOT USE CONTAMINATED CLOTHING AND LAUNDER BEFORE REUSE.DISCARD OIL-SOAKED SHOES.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NEEDED WHEN THERE IS ADEQUATE VENTILATION:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGAINIC VAPORS/MIST,IF ABOVE TLV.

Ventilation:USE LOCAL EXHAUST TO CAPTURE FUMES AND VAPORS.

Protective Gloves:CHEMICAL RESISTANT/RUBBER

Eye Protection:SPLASH GOGGLES/FACE SHIELD

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Work Hygienic Practices:AVOID CONTACT WITHEYES AND SKIN DO NOT BREATHE VAPORS/MIST.WASH THOROUGHLY AFTER EACH USE.

Supplemental Safety and Health

MSDS DATED:4/16/79;MSDS SUPPLIED BY OCTAGON PROCESS (DISTIRIBUTOR)

===== Physical/Chemical Properties =====

=====

HCC:V6

Boiling Pt:B.P. Text:550F/288C

Vapor Pres:12.0

Spec Gravity:0.876

Evaporation Rate & Reference: