

DAVIS HOWLAND OIL CORPORATION -- VVL-825,TYPE I:CODE #01567 -- 9150-00-664-4447
===== Product Identification =====

Product ID:VVL-825,TYPE I:CODE #01567

MSDS Date:01/01/1987

FSC:9150

NIIN:00-664-4447

MSDS Number: BFKNX

=== Responsible Party ===

Company Name:DAVIS HOWLAND OIL CORPORATION

Address:200 ANDERSON AVENUE

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Info Phone Num:716-473-6650

Emergency

Phone Num:716-473-6650

CAGE:5A565

=== Contractor Identification ===

Company Name:DAVIS HOWLAND OIL CORP.

Address:200 ANDERSON AVE.

City:ROCHESTER

State:NY

ZIP:14607

Country:US

Phone:716-473-6650

CAGE:5A565

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM (CRUDE OIL), (OSHA PEL IS FOR PETROLEUM
DISTILLATE AND ACGIH TLV IS FOR RUBBER SOLVENT)

CAS:8002-05-9

RTECS #:SE7175000

Fraction by Wt: 100.0%

Other REC Limits:5MG/CUM,OIL MIST

OSHA PEL:400 PPM

ACG

=====
===== Hazards Identification =====

LD50 LC50 Mixture:ORAL,RAT >5G/KG;DERMAL RABBIT>3G/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Health Hazards Acute and Chronic:SLIGHTLY IRRITATING TO EYES,SKIN AND
RESPIRATORY TRACT.NO CHRONIC EFFECTS ARE KNOWN.
Effects of Overexposure:EYES:SLIGHT IRRITATION. SKIN:SLIGHT IRRITATION.
RESPIRATORY SYSTEM:MINIMALLY IRRITATING.

=====
===== First Aid Measures =====

=====
First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF
NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

=====
===== Fire Fighting Measures =====

Flash Point Method:COC
Flash Point:330F/166C
Extinguishing Media:CO*2, FOAM, DRY CHEM & H*2O FOG.
Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H*2O SPRAY TO COOL
CONTR.
Unusual Fire/Exp
losion Hazard:NONE INDICATED

=====
===== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;CONTAIN SPILL
IF POSSIBLE,WIPE UP OR ABSORB ON SUITABLE ABSORBENT MATERIAL AND
RECOVER FOR PROPER DISPOSAL.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED
AREA.KEEP AWAY FROM HEAT,OPEN FLAMES AND SPARKS.
Other Precautions:WATER CONTAMINATION S

HOULD BE AVOIDED.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS IF ABOVE TLV.

Ventilation:MECH(GEN)OR LOCAL EXHAUST THAT PROVIDES ADEQUATE VENTILATION

Protective Gloves:NEOPRENE

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:FULL WORK CLOTHING TO PREVENT REPEATED OR PROLONGED CONTACT.

Work Hygienic Practices:AVOID CONTACT WITH EYES AND SKIN.DO NOT BREATHE VAPORS,WAS

H THOROUGHLY AFTER USE.DO NOT USE CONTAMINATED CLOTHES.

Supplemental Safety and Health

MSDS UNDATED.

===== Physical/Chemical Properties =====

HCC:V6

Spec Gravity:0.9013

Appearance and Odor:LIGHT PALE LIQUID

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE NOTED

Stability Condition to Avoid:EXTREME HEAT,OPEN FLAMES,SPARKS

Hazardous Decomposition Products:THERMAL COMBUSTION

PRODUCT,CO,CO*2,ALDEHY
DE & KETONES;COMBUSTION PRODUCT OF N*2 AND
SULFUR.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to

be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.