

PRATT & LAMBERT, INC. -- ENAMEL ALKYD GLOSS WHITE 17875 -- 8010-00-664-4761

=====
Product Identification
=====

Product ID:ENAMEL ALKYD GLOSS WHITE 17875

MSDS Date:03/22/1988

FSC:8010

NIIN:00-664-4761

MSDS Number: BFKPN

=== Responsible Party ===

Company Name:PRATT & LAMBERT, INC.

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Preparer's Name:W.A. ELLISON

CAGE:FO127

===

Contractor Identification ===

Company Name:PRATT & LAMBERT, INC/BUFFALO, NY 14240

Box:22

CAGE:FO127

Company Name:PRATT AND LAMBERT INC

Address:Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:VM&P NAPHTHA (LIGROINE)

CAS:8032-32-4

RTECS #:OI6180000

OSHA PEL:300 PPM/400 STEL

ACGIH TLV:300 PPM; 9192

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

OSHA PEL:15 MG/

M3 TDUST
ACGIH TLV:10 MG/M3 TDUST; 9293

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SWALLOWING: CAN CAUSE GASTROINTESTINAL
IRR/NAUSEA/VOMIT. ASPIRATION OF MAT'L MAYCAUSE CHEM PNEUMONITIS.
INHALATION: NOSE/THROAT IRRITA. HIGH CONCENTRATION MAY CAUSE
CENTRAL NERVOUS SYSTEM DEPRESSION CHAR BY
HEADACHES/DIZZINESS/N
AUSEA/CONFUSION. EYE: MAY CAUSE EYE IRR. SKIN:
MAY CAUSE DEFATTING AND IRRITATION.
Effects of Overexposure:REPORTS HAVE ASSOCIATED PROLONGED AND REPEATED
OCCUPATIONAL OVEREXPOSURE TO SOLVENTS WITH PERMANENT BRAIN AND
NERVOUS SYSTEM DAMAGE. INTENTIONAL MISUSE BY DELIBERATELY
CONCENTRATING AND INHALING THE CONTENTS MAY BE HARMFUL OR FATAL.

=====
First Aid Measures
=====

First Aid:SWALLOWING: DO NOT INDUCE VOMITING/GET MED ATTN. INHALATIO
N:
REMOVE TO FRESH AIRIF BREATHING HAS STOPPED GIVE CPR. GET MED ATTN.
EYE: FLUSH W/WATER FOR 15 MIN LIFTING UPPER/LOWER LIDS. GET MED
ATTN. SKIN: REMOVE CONTAMINATED CLOTHING.WASH AFFECTED AREA.
OBTAIN MED ATTN IF IRR'N PERSISTS. TREATMENT REQ FOR OVER-
EXPOSURE S/B DIRECTED AT THE CONTROL OF SYMPTOMS AND THE CLINICAL
CONDITIONS.

=====
Fire Fighting Measures
=====

Flash Point Method:SCC
Flash Point:>102F 38.89C
Extinguishing Media:U
SE NFPA CLASS B FIRE EXTINGUISHERS. POLYMER FOAM
IS PRE- FERRED FOR LARGE FIRES.
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS. WATER
TO COOL CONT TO PREVENT POSSIBLE AUTO-IGNITION OR EXPLOSION. IF
WATER IS USED, FOG NOZZLES ARE PREFERABLE.
Unusual Fire/Explosion Hazard:ISOLATE FROM HEAT/ELEC
EQUIP/SPARKS/FLAME. CONT MAY EXPLODE WHEN EXPOSED TO HEAT.
OVEREXPOSURE TO DECOMP PRODUCTS MAY CAUSE HEALTH HAZ. OBTAIN MED
ATTN.

=====
Accide
=====

ntal Release Measures =====

Spill Release Procedures:ELIM ALL IGNITION SOURCES. DIKE/CONTAIN SPILL WITHINERT MAT'L. TRANSFER LIQ'S/ABSORBENT DIKING MAT'L IN COVERED METAL CONT'S FOR RECOVERY/DISPOSAL. USE ONLY NON-SPARKING TOOLS. PREVENT CONTAM OF SEWERS/ STREAMS/GROUNDWATER W/SPILLED MAT'L/USED ABSORBENT

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 95F. STORE LARGE QUANTITIES IN COMPLIA NCE WITH OSHA 29CFR1910.106.

Other Precautions:DO NOT REUSE EMPTY CONTAINERS. DO NOT TAKE INTERNALLY. CONTAINER SHOULD BE GROUNDED AND BONDED TO THE RECEIVING CONTAINER. DO NOT WELD/BRAZE OR CUT CONT'R.NEVER USE PRESSURE TO EMPTY. DRUM IS NOT A PRESSURE VESSEL. CLOSE AFTER EA USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:WELL VENTILATED AREA-RESP NOT REQ. RESTRICTED VENT-NIOSH CHEMICAL CARTRIDGE MAY BE REQ. IF SPRAYING, ME CH

PREFILTER MAY BE REQ. IF TLV ARE EXCEEDED, USE A PROP FITTED NIOSH/MSHA RESP W/APPROP PROTECTI ON FACTOR. SEE OSHA 29 CFR 1910.134.

Ventilation:PROVIDE DILUT/LOCAL EXH VENT TO KEEP CONCENT OF HAZ INGRID BELOW EXPOSURE LMT STD. REMOVE PROD GEN-WELD/CUT/BRAZ OBJECT

Protective Gloves:SOLVENT IMPERMEABLE GLOVES.

Eye Protection:WEAR SAFETY SPECTACLES.

Other Protective Equipment:NOT LIKELY TO BE NEEDED.

Work Hygienic Practices:WASH WITH SOAP AND WATER HANDS/FACE THOROUGHLY BEFOR

E EATING OR DRINKING.

Supplemental Safety and Health

NK

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:280F 388F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER.

Percent Volatiles by Volume:57

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES STRONG ACIDS OR ALKALINE MATERIALS.

Stability Condition to Avoid:AVOID EXCESSIVE HEAT AND SOURCES OF IGNITION.

Hazar

dous Decomposition Products: BURNING, INCLUDING WHEN HEATED BY WELDING/CUTTING WILL PRODUCE SMOKE/CARBON MONOXIDE/CARBON DIOXIDE.

Conditions to Avoid Polymerization: KEEP AWAY FROM HEAT, SPARKS AND FLAME.

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE ONLY IN EPA PERMITTED FACILITY. DISPOSE ONLY IAW FED/STATE/LOCAL REGS. DO NOT INCINERATE CLOSED CONTAINERS. OBSERVE PRECAUTIONS FOR DISPOSAL OF FLAMMABLE MAT'S. CONTAMINATED ABSORBENT MAY BE DISPOSED IN A HAZARDOUS WASTE LANDFILL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.