

PRATT & LAMBERT-WICHITA DIVISION -- 726-002 -- 8010-00-664-6302

=====  
Product Identification  
=====

Product ID:726-002

MSDS Date:01/01/1987

FSC:8010

NIIN:00-664-6302

MSDS Number: BFKQZ

=== Responsible Party ===

Company Name:PRATT & LAMBERT-WICHITA DIVISION

Emergency Phone Num:316-733-1361

CAGE:KO010

=== Contractor Identification ===

Company Name:PRATT & LAMBERT-WICHITA DIV.

Box:2153

CAGE:KO010

Com

pany Name:PRATT AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 35.0%

OSHA PEL:100 PPM

=====  
Hazards Identification  
=====

Effects of Overexposure:INHALED:ANESTHETIC,IRRIT.AIRWAY;SKIN/EYE  
IRRIT.HEADACHE,DIZZINESS, COMA, CONFUSION.

===

=====  
First Aid Measures  
=====

First Aid:INCASE OF CONTACT,FLUSH SKIN AND EYES WITH PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING.IN INHALED, REMOVE TO FRESH AIR.CALL DR. IF SYMPTONS PERSIST. PERFORM ARTIF.RESP. IF BREATHING HAS STOPP ED.

=====  
Fire Fighting Measures  
=====

Flash Point:104F, 40 C TCC

Lower Limits:1.1

Extinguishing Media:CARBON DIOXIDE/DRY CHEM.SMALL;POLYMER FOAM-LARGE FIRE

Fire Fighting

Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE FOR FIREMEN

Unusual Fire/Explosion Hazard:PRESSURE BUILD-UP FROM EXTREME HEAT MAY CAUSE EXPLOSION.USE WATER TO COOL CANS.FOR FIRE: FOG NOZZLES

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES, HOT SURFACES,& ELECTRICAL,OR FRICTIONAL SPARKS).AVOID BREATHING VAPORS. VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

=====

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE AMTS.INBUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS ONE FLAMMABLE(OR COMBUSTIBLE)LIQUID.

Other Precautions:DO NOT TAKE INTERNALLY,CONTAINERS SHOULD BE GROUNDED WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES,DO NOT FLAME CUT,BRAZE,OR WELD COATED MATERIAL WITHOUT VENTILATION.

=====  
Exposure Controls/Personal Protection  
=====

=====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY & WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:USE EYEWEAR IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.

Supplemental Safety and Health

BOILING RANGE 155-189 C.

=====  
Physical/Chemical Properties  
=====

HCC:F4

Boiling Pt:B.P. Text:311-373F

Eva

poration Rate & Reference:< ETHER

Appearance and Odor:WHITE

Percent Volatiles by Volume:60.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:FIRES,HEAT, & HOT

SURFACES,SPARKS,ELECTRICAL EQUIP.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IAW LOCAL,STATE,AND

FED.REGULATIONS.INCINERATE IN APPROVED FACILITY. DO NOT INCINERATE

CLOSED CO

NTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.