

DESANTIS COATINGS, INC -- L-299,TRAFFIC PAINT,YELLOW -- 8010-00-664-7047

=====
Product Identification
=====

Product ID:L-299,TRAFFIC PAINT,YELLOW

MSDS Date:01/01/1985

FSC:8010

NIIN:00-664-7047

MSDS Number: BFKRZ

=== Responsible Party ===

Company Name:DESANTIS COATINGS, INC

Emergency Phone Num:(216)946-0300

CAGE:DESAN

=== Contractor Identification ===

Company Name:DESANTIS COATINGS,INC

Box:160

Cit

y:WILLOUGHBY

State:OH

ZIP:44094-0160

Country:US

CAGE:DESAN

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 17.2%

OSHA PEL:100 PPM

Ingred Name:ALKYD RESIN (PERCENT UNKNOWN)

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt: 10.1%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05MG/M3(CR)A2;8990

=====
Hazards Identification
=====

Effects of Overexposure:INHAL:IRRIT OF RESP TRACT OR ACUTE CNS
DEPR-HEADACHE, DIZZ, CNFUSN, STAG, UNCONSC, OR COMA.

=====
First Aid Measures
=====

First Aid:INHAL:MOVE TO FRESH AIR.RESTORE BREATHING IF NEC. KEEP WRM &
QUIET. CALL MD. EYE:IMMEDIATELY FLUSH W/WATER AT LEAST 15 MIN TAKE
TO MD.

=====
Fire Fighting Measures
=====

Flash Point:5

2F TCC

Lower Limits:1.4

Upper Limits:6.8

Extinguishing Media:CO*2, DRY CHEMICA,FOAM-CLASS B EXTINGUISHERS

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS MAY EXPLODE WHEN
EXPOSED TO EXTREME HEAT.

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING
VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBENT AND NON-SPARKING
TOOLS.

=====
Handling and Storage
=====

Handlin

g and Storage Precautions:DO NOT STORE ABOVE 120F. WASH HANDS
THOROUGHLY AFTER HANDLING PRODUCT.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:IN RESTRICTED VENTILATION-NIOSH/MSHA APPROVED
CHEMICAL-MECH. FILTER.

Eye Protection:SAFETY EYEWEAR

Supplemental Safety and Health

VAPOR DENSITY:HEAVIER THAN AIR.MFG ADDRESS:DESANTIS COATINGS INC,4580
BEIDLER ROAD,WILLOUGHBY,OHIO 44094.SPECIFICATION REQUIRES 62%(BY
WEIGHT) OF PAINT TO BE PIGMEN

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:244 TO 287F

Vapor Pres:15

Spec Gravity:1.70

Evaporation Rate & Reference:0.9

Solubility in Water:NEGLIGIBLE

Appearance and Odor:YELLOW PAINT

Percent Volatiles by Volume:39.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:THERMAL DECOMP - CO, CO*2, LAD OXIDE &
CHROMIUM OXIDE

=====

==== Disposal Considerations =====

Waste Disposal Methods:IN ACCORDANCE W/LOCAL,STATE & FEDERAL
REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person uti
lizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.