

RED DEVIL INCORPORATED -- INSTANT WOOD FILLER (0521, 0522, 0528) -- 8010-00-664-7088

=====
Product Identification
=====

Product ID:INSTANT WOOD FILLER (0521, 0522, 0528)

MSDS Date:02/28/1986

FSC:8010

NIIN:00-664-7088

MSDS Number: BFKSX

=== Responsible Party ===

Company Name:RED DEVIL INCORPORATED

Address:WEBB STREET

Box:A

City:PRYOR

State:OK

ZIP:74362

Info Phone Num:918 825 5744

Emergency Phone N

um:918 825 5744 (24 HRS)

CAGE:DO902

=== Contractor Identification ===

Company Name:RED DEVIL INCORPORATED

Address:WEBB STREET

Box:A

City:PRYOR

State:OK

ZIP:74362

Country:US

CAGE:DO902

Company Name:RED DEVIL, INCORPORATED

Address:ONE WEBB STREET

Box:A

City:PRYOR

State:OK

ZIP:74361

Country:US

Phone:918-825-5744

CAGE:23577

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt:

Other REC Limits:N/K

OSHA

PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt:
Other REC Limits:N/K
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt:
Other REC Limits:N/K
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:HEXYLENE GLYCOL
CAS:107-41-5
RTECS #:SA0810000
Fraction by Wt:
Other REC Limits:N/K
OSHA PEL:C 25 PPM
ACGIH TLV:C 25 PPM; 9192

Ingred Name:WOOD FLOUR (MFR TLV AS WOOD DUST. INHALATION OF
PARTICULATES UNLIKELY DUE TO PRODUCTS PHYSICAL STATE).
Fraction by Wt:
Other REC Limits:TLV=1 MG/CUM
OSHA PEL:N/K
ACGIH TLV:N/K

Ingred Name:DI-SEC-OCTYL PHTHALATE (DI-2-ETHYLHEXYL-PHTHALATE) (SARA
III)
CAS:117-81-7
RTECS #:TI0350000
Fraction by Wt:
Other REC Limits:N/K
OSHA PEL:5 MG/

M3/10 STEL
ACGIH TLV:5 MG/M3; 9192
EPA Rpt Qty:100 LBS
DOT Rpt Qty:100 LBS

Ingred Name:NON-HAZARDOUS INGREDIENTS (UNLISTED INGREDIENTS NOT
CONSIDERED HAZ UNDER FED HAZ COMM STANDARD (29 CFR 1910.1200))

Fraction by Wt:
Other REC Limits:N/K
OSHA PEL:N/K
ACGIH TLV:N/K

=====
Hazards Identification
=====

LD50 LC50 Mixture:N/K
Reports of Carcinogenicity:NTP:YES IARC:YES OSHA:NO
Health Hazards Acute and Chronic:(SEE SIGNS & SYMPTOMS OF OVEREXPOSURE)
Ex
planation of Carcinogenicity:DI-SEC,OCTYL PHTHALATE:NTP:ANTICIPATED
CARC.IARC:HUMAN CARC(GRP 2B).NTP:SHOWN TO CAUSE CANCER IN LAB
ANIMALS(MFR).
Effects of Overexposure:INHALATION OF DUST GENERATED FROM DRIED PRODUCT
MAY CAUSE RESPIRATORY IRRITATION. HIGH VAPOR CONCENTRATIONS MAY
PRODUCE HEADACHE,DIZZINESS & NAUSEA. PROLONGED OR REPEATED SKIN
CONTACT MAY LEAD TO DRYI NG & IRRITATION. EYE CONTACT CAUSES
BURNING & IRRITATION. MAY CAUSE MINOR REVERSIBLE EFFECTS UPON LIVER
& KIDNEY.
Medical Cond Aggravated by Exposure:N/K

=====
First Aid Measures
=====

First Aid:EYES:IMMEDIATELY FLUSH EYES W/LARGE AMOUNTS OF H*2O FOR AT
LEAST 15 MINUTES WHILE HOLDING EYELIDS OPEN. GET PROMPT MEDICAL
ATTENTION. SKIN:WIPE MATERIAL FROM SKIN W/CLOTH OR PAPER TOWEL,
THEN WASH EXP OSED AREA W/SOAP & WATER. GET MEDICAL HELP IF
IRRITATION PERSISTS. INHALATION:MOVE VICTIM TO FRESH AIR & TREAT
SYMPTOMATICALLY. INGESTION:CONTACT
LOCAL POISON CONTROL CENTER OR
PHYSICIAN IMMEDIATELY.

=====
Fire Fighting Measures
=====

Flash Point:40 F (4 C)
Lower Limits:N/E
Upper Limits:N/E
Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, OR FOAM
Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT . USE WATER SPRAY OR FOG TO COOL FIRE-EXPOSED CONTAINERS.
Unusual Fire/Explosion Hazard:VAPORS CAN FLOW TO IGNITION SOURCES AND
FLASHBACK.

=====
Accide

ntal Release Measures =====

Spill Release Procedures:WIPE UP SPILLED MATERIAL. WASH AREA WITH DETERGENT.

Neutralizing Agent:N/K

===== Handling and Storage =====

Handling and Storage Precautions:FLAMMABLE. STORE IN CLOSED CONTAINER IN COOL, WELL-VENTILATED AREA.

Other Precautions:N/K

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESPIRATOR APPROPRIATE FOR EXPOSURE O

F CONCERN . NOT NORMALLY REQUIRED. IF TLV IS EXCEEDED, OR FOR SYMPTOMS OF OVEREXPOSURE, WEAR A NIOSH-APPROVED RESPIRATOR FOR ORGANIC VAPO RS.

Ventilation:LCL EXHAUST MAY BE NECESSARY UNDER SOME HANDLE/USE CONDTN.SUPERVISORY/HEALTH/SAFETY PERS SHOULD ADDRESS SPECIFIC NEEDS.

Protective Gloves:CHEMICAL-RESISTANT GLOVES

Eye Protection:CHEMICAL WORKERS GOGGLES

Other Protective Equipment:WEAR CHEMICAL-RESISTANT GLOVES & CLOTHING AS NEEDED TO PREVENT SKIN CONTACT.

Work Hygienic Pra
ctices:N/K

Supplemental Safety and Health

N/E=NOT ESTABLISHED. PH, FLASH PT METHOD, ROUTES OF ENTRY & CARCINOGENITY:FP N.PRODUCT REFORMULATED FIVE YEARS AGO.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:N/E

Melt/Freeze Pt:M.P/F.P Text:N/K

Decomp Temp:Decomp Text:N/K

Vapor Pres:N/E

Vapor Density:>1

Spec Gravity:N/E

Evaporation Rate & Reference:>1, BUAC=1

Solubility in Water:INSOLUBLE

Appearance and Odor:PASTE; SOLVENT ODOR

Percent V

Volatiles by Volume:31
Corrosion Rate:

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZERS.

Stability Condition to Avoid: NORMALLY STABLE. AVOID HEAT, SPARKS, OPEN FLAME.

Hazardous Decomposition Products: CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.