

SENTRY PAINT COMPANY -- X-5767, ALUMINUM HT RES 1200DEG -- 8010-00-664-7468

=====
Product Identification
=====

Product ID:X-5767, ALUMINUM HT RES 1200DEG

MSDS Date:05/18/1993

FSC:8010

NIIN:00-664-7468

MSDS Number: BFKTH

=== Responsible Party ===

Company Name:SENTRY PAINT COMPANY

Address:237 MILL ST

City:DARBY

State:PA

ZIP:19023-0272

Country:US

Info Phone Num:215-522-1900

Emergency Phone Num:800-4

24-9300(CHEMTREC)

CAGE:LO232

=== Contractor Identification ===

Company Name:SENTRY PAINT AND CHEMICAL CO

Address:MILL AND LAWRENCE ST

Box:City:DARBY

State:PA

ZIP:19023

Country:US

CAGE:34346

Company Name:SENTRY PAINT COMPANY

Address:237 MILL ST.

City:DARBY

State:PA

ZIP:19023

Country:US

CAGE:LO232

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 49.2%

OSHA PEL:100 PPM

Ingred Nam

e:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 10%

OSHA PEL:100 PPM

=====
===== Hazards Identification =====

Effects of Overexposure:EYE/SKIN:IRRIT/DEFAT. VAPORS:NASAL & RESP
IRRIT, ASPHYXIATION. INGESTION:GI IRRI,CHEM PNEUMONITIS

=====
===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER 15 MINUTES, CONSULT PHYSICIAN. SKIN:WASH
WITH SOAP & WATER,REMOVE & WASH CONTAMINATED CL
OTHING BEFORE REUSE.

INGESTION:DO NOT INDUCE VOMITING,GET MEDICAL ATTN.

INHALATION:REMOVE T O FRESH AIR,GIVE ARTIF RESP,GET MEDICALATTN.

=====
===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:54.0F,12.2C

Autoignition Temp:Autoignition Temp Text:480F

Lower Limits:0.8% & INGS

Extinguishing Media:FOAM, CO*2, DRY CHEM,(WATER MAYBE INEFFECTIVE).

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA & FULL PROTECTIVE
EQUIPMENT . COOL CLOSED
CONTAINERS W/WATER SPRAY.

Unusual Fire/Explosion Hazard:CLSD CNTNRS MAY BUILD EXPLO PRESS FROM
HEAT. VAPS ARE HVR/AIR & MAY TRAVEL ALONG GROUND/MAY BE MOVED BY
VENT & IGNITED BY PILOT LIGHTS, OTHER FLAMES, (SUPDAT)

=====
===== Accidental Release Measures =====

Spill Release Procedures:SHUT OFF LEAK,SECURE IGNITION SOURCES. EXCLUDE
PERSONNEL WITHOUT PROPER PROTECTIVE EQUIPMENT & RESPIRATORS FROM
AREA. DIKE SPILL WITH INERT MATERIAL. PICK UP WITH NON-SPARKI

NG
TOOLS. KEEP OUT OF SEWER S & OPEN BODIES OF WATER.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP OUT OF SUN & AWAY FROM HEAT.
GROUND CONTAINER WHEN POURING,LIMIT FREE FALL OF LIQUID TO A FEW
INCHES. KEEP DRUM CLOSED & UPRIGHT,WHEN NOT IN USE.

Other Precautions:DO NOT CUT,PUNCTURE OR WELD ON OR NEAR
CONTAINER,EMPTY CONTAINER MAY CONTAIN EXPLOSIVE VAPORS OR DANGEROUS
RESIDUE. KEEP FROM SOURCES OF IGNITION.

=====

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN.
Ventilation:MECHANICAL OR LOCAL EXHAUST TO MAINTAIN EXPOSURE BELOW TLV.
Protective Gloves:WEAR RESISTANT
Eye Protection:CHEM SPLASH GOGGLES
Other Protective Equipment:EYE WASH,SHOWER,LONG SLEEVE & LEG CLOTHING.
Supplemental Safety and Health
CONTAINER SIZE: 1 QT

===== Physical/Chemical Properties =====

Boiling
Pt:B.P. Text:>246F,>119C
Vapor Pres:SEE INGS
Vapor Density:>1
Spec Gravity:0.99
Viscosity:54-67 KU@77F
Evaporation Rate & Reference:SLOWER/ETHER
Appearance and Odor:ALUMINUM COLOR PAINT.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID CONT W/STRONG OXIDIZING AGENTS, WATER, MINERAL ACIDS, HARSH ALKALIS, HALOGENATED CMPDS. THIS MATL REACTS (SUPDAT)
Stability Condition to Avoid:EXCESSIVE HEAT, SPARKS & OPEN FLAME.
Hazar
dous Decomposition Products:CO,CO*2, VARIOUS
HYDROCARBONS,ACROLEIN,ETC

===== Disposal Considerations =====

Waste Disposal Methods:BY METHODS CONSISTENT WITH LOCAL,STATE AND FEDERAL REGULATIONS FOR LIQUID & CONTAMINATED DIKING MATERIAL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly

or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.