

EASTMAN KODAK COMPANY -- 194 7738,HARDENER,PROCESS C-22,PART B -- 6750-00-680-7877

=====
Product Identification
=====

Product ID:194 7738,HARDENER,PROCESS C-22,PART B

MSDS Date:01/01/1987

FSC:6750

NIIN:00-680-7877

Kit Part:Y

MSDS Number: BFLHQ

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5

151

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====
Composition/Information on Ingredients
=====

Ingred Name:FORMALDEHYDE (SARA III)

CAS:50-00-0

RTECS #:LP8925000

Fraction by Wt: 35-40%

OSHA PEL:SEE 1910.1048

ACGIH TLV:C 0.3 PPM; A2; 9293

EPA Rpt Qty:100 LBS

DOT R

pt Qty:100 LBS

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 10-15%

Other REC Limits:ACGIH STEL 250 PPM

OSHA PEL:S,200PPM/250STEL

ACGIH TLV:S,200PPM/250STEL; 93

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:WATER

CAS:7732-18-5

RTECS #:ZC0110000

Fraction by Wt: 50-55%

=====
===== Hazards Identification =====

Effects of

Overexposure:INHALE:IRRITNT(VAPOR);EYES:IRRITNT(VAPOR);BURNS(LIQUID);SKIN:IRRITNT (LIQ),ALLERGIC SKIN REACTION.

=====
===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR,GIVE CPR/O*2 IF NEED;EYES:FLUSH W LG AMTS H*2O FOR 15 MIN;SKIN:FLUSH W LG AMTS H*2O;INGEST:RINSE MOUTH;GET IMMEDIATE MEDICAL ATTN FOR EYES OR INGEST.

=====
===== Fire Fighting Measures =====

Flash Point:146F,63C TCC

Lower Limits:7.0

Upper Limits:73

Extinguishing Media:WATER,DRY CHEMICAL,CARBON DIOXIDE.

Fire Fighting Proced

ures:WEAR SCBA & PROTECTV CLOTHG TO PREVENT SKIN/EYE CONTACT.

Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PROUDCTS.

=====
===== Accidental Release Measures =====

Spill Release Procedures:WEAR APPROPRIATE PROTECTIVE EQUIPMENTS. STOP LEAK W/O RISK. DIKE LIQUID W/ABSORBENT & TRANSFER LIQ TO SALVAGE TANK. MFR SUGGESTS TO FLUSH MATERIAL TO AN ACID-FREE SEWER WITH LARGE AMOUNTS OF WATER.

=====

==== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED, LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE. AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED.

Other Precautions:AVOID PROLONGED OR REPEATED CONTACT W CHEMICAL. REMOVE & WASH CONTAMINATED CLOTHING. MAINTAIN STRICT HYGIENE. KEEP COOL. STORE AWAY FROM HCL OR STRONG OXIDANTS. MAX TEMPERATURE: 120F.

==== Exposure Controls/Personal Protection ==

=====

Respiratory Protection:FOR EXPOSURE:SELF-CNTND BRTHG APP/APPR RESPIRATOR(ORGANIC VAPORS).

Ventilation:MECHANICAL(GEN./LOCAL EXHAUST)

Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY/CHEM GOGGLES.

Other Protective Equipment:NORMAL FULL WORK CLOTHING COVERING ARMS, LEGS:NO SKIN CONTACT

Supplemental Safety and Health

KEY 1: X01; CSDS FROM KODAK DATED: 12/10/68, ADDENDUM TO MSDS DATED: 3/11/81; PH OF SOLN: 7.0; THIS IS PART B (FIXER) OF HARDENER KIT (KIT ALSO CONTAINS D

EVELOPER, STOP BATH, BLEACH HARDENER-SEE OTHER PNI). KEY 1: F8

==== Physical/Chemical Properties =====

HCC:V4

Boiling Pt:B.P. Text:146F/63C

Vapor Pres:17

Spec Gravity:1.08

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR AQUEOUS MIXTURE; TYPICAL FORMALDEHYDE ODOR.

Percent Volatiles by Volume:100

==== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MINERAL ACIDS, STRONG OXIDIZERS

Stability Conditio

n to Avoid:EXCESSIVE HEAT

Hazardous Decomposition Products:THERMAL DECOMPOSITION WILL EMIT OXIDES OF CARBON.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED DRUMS,PENDING DISPOSAL.HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL,FEDERAL,STATE,& LOCAL REGULATIONS.MFG SUGGESTS FLUSH TO SEWER WITH EXCESS WATER.

Disclaimer (provided with this information by the compiling agencies):

This information i

s formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.