

EASTMANK KODAK COMPANY -- 194 7738, FIXER, PROCESS C-22 -- 6750-00-680-7877

===== Product Identification =====

Product ID: 194 7738, FIXER, PROCESS C-22

MSDS Date: 01/01/1985

FSC: 6750

NIIN: 00-680-7877

MSDS Number: BFLHS

=== Responsible Party ===

Company Name: EASTMANK KODAK COMPANY

Emergency Phone Num: 716-722-5151

CAGE: 5K871

=== Contractor Identification ===

Company Name: EASTMAN KODAK CO GOVERNMENT MARK

ETS CONTRACTS

Address: 343 STATE ST

Box: City: ROCHESTER

State: NY

ZIP: 14650-1115

Country: US

Phone: 716-722-5151 / (800) 242-2424

CAGE: 19139

Company Name: EASTMAN KODAK CO US CUSTOMER SERVICE/GOVERNMENT SALES

Address: 800 LEE RD

Box: City: ROCHESTER

State: NY

ZIP: 14650-3129

Country: US

Phone: 800-828-6203

CAGE: 5K871

===== Composition/Information on Ingredients =====

Ingred Name: SODIUM THIOSULFATE (CAS #7772-98-7) (95-100%)

CAS: 7772-98-7

RTECS #: XN6476000

Fraction by Wt: 100%

=====

===== Hazards Identification =====

Effects of Overexposure:LOW HEALTH HAZARD

===== First Aid Measures =====

First Aid:MFR SUGGESTS NONE INDICATED,BUT GOOD INDUSTRIAL HYGIENE SHOULD BE FOLLOWED.EYES:FLUSH WITH WATER 15 MIN.SKIN:WASH WITH SOAP & WATER.GET MEDICAL ATTENTION IF SYMPTOMS PERSIST.INHALED:REMOVE TO FRESH AI R.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE I  
GNITION SOURCES.SWEEP UP AND PLACE  
IN CONTAINER.FLUSH RESIDUR TO SEWER WITH COPIOUS AMOUNTS OF  
WATER.STATE AND LOCAL EFFLUENT LAWS TAKE PRECEDENCE.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY WELL-VENTED,LOW FIRE  
DISK AREA.PROTECT FROM PHYSICAL DAMAGE.KEEP CONTAINERS CLOSED.AVOID  
PROLONGED OR REPEATED CONTACT.  
Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Re  
spiratory Protection:NONE NORMALLY NEEDED  
Ventilation:MECHANICAL(GENERAL)  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY/CHEMICAL GOGGLES  
Other Protective Equipment:NORMAL WORK CLOTHING COVERING  
ARMS,LEGS;SAFETY SHOES.  
Supplemental Safety and Health  
ITEM CONSISTS OF 5 PARTS (BLEACH, DEVELOPER, FIXER, HARDENER A & B &  
STOP BATH). THIS DEXCRIBES FIXER. SEE OTHER PNI THIS NSN. MSDS FOR  
THIS PART FM MFR DATED: 3/11/81. KEY 1: N1

===== Physical/Chemical Properties =====

=====

HCC:N1  
Vapor Pres:NEG  
Spec Gravity:>1  
Solubility in Water:APPRECIABLE  
Appearance and Odor:WHITE,ODORLESS POWDER  
Percent Volatiles by Volume:NEG

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
STRONG MINERAL ACIDS  
Hazardous Decomposition Products:SULFUR DOIXIDE

===== Disposal Considerations =====

Waste Disposal Methods:PLACE SOLID IN CONTAINER FOR TRANSPORT TO  
DISPOSAL SITE.DISPO  
SE IN ACCORDANCE WITH ALL APPLICABLE  
FEDERAL,STATE,AND LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume resp  
onsibility for the suitability of this information to their  
particular situation.