

INMONT CORP.,PRESSTITE PRODUCT -- PRESSTITE 579.6 PLASTIC SEALER -- 8030-00-683-9014

=====
Product Identification
=====

Product ID: PRESSTITE 579.6 PLASTIC SEALER
MSDS Date: 01/01/1985
FSC: 8030
NIIN: 00-683-9014
MSDS Number: BFLNB
==== Responsible Party ====
Company Name: INMONT CORP., PRESSTITE PRODUCT
Emergency Phone Num: 314-664-6000
CAGE: LO807
==== Contractor Identification ====
Company Name: INMONT CORP
P
Address: 3738 CHOUTEAU AVE
Box: City: ST LOUIS
State: MO
ZIP: 63110-2546
Country: US
CAGE: 77464
Company Name: INMONT CORP., PRESSTITE PRODUCT
CAGE: LO807

=====
Composition/Information on Ingredients
=====

Ingred Name: NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

=====
First Aid Measures
=====

First Aid: IF SWALLOWED CALL A DR.

=====
Fire Fighting Measures
=====

Flash Point: >300 F COC >149
Extinguishing Media:
CLASS ABC
Fire Fighting Procedures: NORMAL

=====
Accidental Release Measures
=====

Spill Release Procedures: REMOVE WITH SPATULA OR PUTTY KNIFE. CLEAN
RESIDUE WITH SAFETY SOLVENT.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: NONE
Ventilation: NORMAL
Supplemental Safety and Health
PROCURED UNDER 579-6 >300 F COC >149 C

=====
Physical/Chemical Properties
=====

HCC: N1
Spec Gravity: 1.24
Solubi

lity in Water:INSOLUBLE
Percent Volatiles by Volume:1

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
SOLUBLE IN PETROLEUM SOLVENTS

===== Disposal Considerations =====

Waste Disposal Methods:BURY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatso-
ever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.