View NSN Online: https://aerobasegroup.com/nsn/8030-00-685-0915

Product ID:GC-408 CLASS B MSDS Date:01/01/1985 FSC:8030 NIIN:00-685-0915 Kit Part:Y MSDS Number: BFLPC === Responsible Party === Company Name: GOAL CHEMICAL SEALANTS CORP. Emergency Phone Num:213-269-0461 CAGE:04011 === Contractor Identification === Company Name: GOAL CHEMICAL SEALANTS CORP Address :3137 E 26TH ST Box:City:LOS ANGELES State:CA ZIP:90023-4206 Country:US Phone:213-269-0461 CAGE:04011

Ingred Name:MANGANESE DIOXIDE (AS MANGANESE) CAS:1313-13-9 RTECS #:OP0350000 Fraction by Wt: 50.0% OSHA PEL:C,5 MG/M3/1 FUME TWA ACGIH TLV:5 MG/M3 DUST/1 FUME

Ingred Name:P-TERPHENYL(TERPHENYL-BIPHENYL,PLASTICIZER) CAS:92-94-4 RTECS #:WZ6475000 Fraction by Wt: 47.0% ACGIH TLV:1 PPM

Ingred Name: GUANIDINE, 1,3-DIPHENYL (DIPHEN

YL GUANIDINE) RTECS #:MF0857000 Fraction by Wt: 3.0%

======================================
Effects of Overexposure: MAY CAUSE SKIN OR EYE IRRITATION; DO NOT INGEST; INHALE: MAY AFFECT SOME PERSONS.
======================================
First Aid:INHALE:REMOVE TO FRESH AIR,GIVE CPR IF NEEDED;SKIN/EYES:FLUSH W LG AMTS H*20(USE SOAP ON SKIN);INGEST:GIVE EMETIC. CALL DR.
======================================
Flash Point:>400F,>204C Extinguishing Media:H*2O,CO*2. Fire Fighting Procedures:SELF-CNTND BRTHG APP. Unusual Fire/Explosion Hazard:COMBUSTION/DECOMPOSITION PRODUCTS INCLUDE H*2S,SO*2,AND OTHER SULFUR COMPOUNDS.
======================================
Spill Release Procedures:MFG. RECOMMENDS SCRAPE UP & CLEAN W KETONES OR TOLUENE. CONSIDERED NON-HAZARDOUS.LIQUID CEMENT. USE APPROVED HANDLING PROCEDURES FOR SPECIFIC SOLVENTS USED FOR CLEANING.
======================================
 Handling and Storage Precautions:STORE IN COOL(50 TO 80F), DRY,VENTILATED, LOW FIRE RISK AREA. PROTECT FROM PHYSICAL DAMAGE. AVOID PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED. Other Precautions:SEE DATA UNDER PN IND A, THIS STOCK NUMBER(TWO PART PRODUCT).
======================================
Respiratory Protection:NONE SHOULD BE NEEDED Ventilation:LOCAL EXHAUST ADEQUATE TO ELIM

INATE ODOR.
Protective Gloves: IMPERVIOUS
Eye Protection: SAFETY/CHEM GOGGLES
Other Protective Equipment: AS REQUIRED; NORMAL WORK CLOTHING GENERALLY ADEQUATE.
Supplemental Safety and Health
OTHER P/N: SCOTCHSEAL 801(B2) IND SLNT. PT A OF TWO PART EC-801 (B2) IND SLNT KIT. 3M GENERIC ID: 62-801-XXXX-X. ADDED INGR: SILICA PIGMENT & WATER. QTY: 1 QT KIT. KEY 1: F4

HCC:N1 Spec Gravity:1.5 Solubility in Water:SLIGHT Appea rance and Odor:OFF WHITE,GREY WHEN MIXED;MERCAPTAN ODOR.

Stability Indicator/Materials to Avoid:YES Stability Condition to Avoid:TEMPERATURE OVER 300F. Hazardous Decomposition Products:SO*2,H*2S,OTHER SULFUR

Waste Disposal Methods:CONSIDERED BY MFG. TO BE NON-HAZARDOUS TRASH. DISPOSE IN FULL REGULATORY COMPLIANCE.

Disclaimer (provided with this informa

tion by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.