

DOW CORNING CORP -- 510 FLUID ALL VISCOSITIES -- 9150-00-718-5290  
===== Product Identification =====

Product ID:510 FLUID ALL VISCOSITIES

MSDS Date:01/01/1985

FSC:9150

NIIN:00-718-5290

MSDS Number: BFMDQ

=== Responsible Party ===

Company Name:DOW CORNING CORP

Emergency Phone Num:517-496-5900

CAGE:5D028

=== Contractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:9

97

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

===== Composition/Information on Ingredients =====

Ingred Name:NON-HAZARDOUS INGREDIENTS

===== Hazards Identification =====

Effects of Overexposure:MAY CAUSE TEMPORARY DISCOMFORT TO EYES

===== Firs

First Aid Measures =====

First Aid:FLUSH WITH WATER

===== Fire Fighting Measures =====

Flash Point:>400F/204C OC

Extinguishing Media:CARBON DIOXIDE OR FOAM

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS &  
PROTECTIVE CLOTHING

Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:USE ABSORBENT MATERIAL TO COLLECT & CONTAIN  
FOR SALVAGE OR DISPOSAL.

==

===== Handling and Storage =====

Handling and Storage Precautions:USE REASONABLE CARE

Other Precautions:TRACE OF BENZENE GENERATED AT HIGH TEMPERATURE.USE  
WITH ADEQUATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED

Ventilation:MECHANICAL

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6

Boi

ling Pt:B.P. Text:>300F

Vapor Pres: