

SEYMOUR OF SYCAMORE -- LACQUER, AEROSOL 12215 ORANGE -- 8010-00-721-9479

=====
Product Identification
=====

Product ID:LACQUER, AEROSOL 12215 ORANGE

MSDS Date:01/01/1985

FSC:8010

NIIN:00-721-9479

MSDS Number: BFMGY

=== Responsible Party ===

Company Name:SEYMOUR OF SYCAMORE

Emergency Phone Num:815-895-9101

CAGE:59581

=== Contractor Identification ===

Company Name:SEYMOUR OF SYCAMORE

Address:917 CR

OSBY AVE.

Box:City:SYCAMORE

State:IL

ZIP:60178-1343

Country:US

Phone:815-895-9101/800-255-3924

CAGE:59581

=====
Composition/Information on Ingredients
=====

Ingred Name:ETHYL ALCOHOL

RTECS #:KJ5075000

Fraction by Wt: 1.75%

ACGIH TLV:1000 PPM

Ingred Name:VM&P NAPHTHA

RTECS #:ZB1600000

Fraction by Wt: 7.00%

ACGIH TLV:300 PPM

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 18.4%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LB

S

DOT Rpt Qty:1000 LBS

Ingred Name:METHYLENE CHLORIDE (DICHLOROMETHANE) (SARA III)

CAS:75-09-2

RTECS #:PA8050000

Fraction by Wt: 24.5%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:500 PPM; Z-2

ACGIH TLV:50 PPM, A2; 9394

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: 0.26%

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
Hazards Id
entification =====

Effects of Overexposure:INHALATION-IRRITATE RESP. TRACT;
HEADACHE,DIZZINESS,CONFUSION MAY BE EYE IRRITANT.

=====
First Aid Measures =====

First Aid:FUMES-REMOVE FROM EXPOSURE, RESTORE BREATHING, NOTIFY
PHYSICIAN. EYES-FLUSH WITH COPIOUS AMOUNTS OF WATER FOR AT LEAST 15
MIN. GET MEDICAL TREATMENT IMMEDIATELY. SKIN-WASH WITH SOAP &
WATER. REMOVE CO NTAMINATED CLOTHING.

=====
Fire Fighting
Measures =====

Flash Point:-10F, AEROSOL

Extinguishing Media:CO2, DRY CHEMICAL OR FOAM

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE WEAR GOGGLES &SELF
CONTAINED RESPIR

Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT MAY CAUSE AEROSOL CAN TO
BURST

=====
Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION, AVOID BREATHING
VAPORS, VENTILATE AREA. WIPE UP WITH INERT MATERIALS & PLACE IN
APPROPRI

ATE CONTAINERS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. EXPOSURE TO HEAT OR PROLONGED EXPOSURE TO SUN MAY CAUSE BURSTING.

Other Precautions:USE ONLY AS DIRECTED. INTENTIONAL MISUSE BY DELIBERATELY CONCENTRATING VAPOR & INHALING CAN BE HARMFUL OR FATAL.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:AVOID CONTINUOUS BREATHING OF VAPORS & SPRAY MIST.

Ventilation:USE WITH ADEQUATE VENTILATION.

Protective Gloves:OPTIONAL

Eye Protection:IF MIST CAN GET INTO EYES

Supplemental Safety and Health

CONTRACT NO. TC-GS-10F-46124

=====
===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:NA

Vapor Density:>AIR

Evaporation Rate & Reference:>ETHER

Percent Volatiles by Volume:85

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to

Avoid:OPEN FLAME

Hazardous Decomposition Products:CO, OXIDES OF NITROGEN, & PHOSGENE

=====
===== Disposal Considerations =====

Waste Disposal Methods:DO NOT INCINERATE AEROSOL. DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE & FEDERAL REGULATIONS. DO NOT PLACE AEROSOL CANS IN HOME COMPACTOR. DO NOT PUNCTURE CANS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense

. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.