View NSN Online: https://aerobasegroup.com/nsn/9330-00-724-3251

AMETEK INC HAVEG DIV -- HAVEG 41-NF CEMENT -- 9330-00-724-3251

Product ID: HAVEG 41-NF CEMENT MSDS Date:02/01/1989 FSC:9330 NIIN:00-724-3251 MSDS Number: BFMMW === Responsible Party === Company Name: AMETEK INC HAVEG DIV Address:900 GREENBANK RD City:WILMINGTON State:DE ZIP:19808-5906 Country:US Info Phone Num:302-995-0400 Emergency Phone Num: 302-995-0496 CAGE:032 00 === Contractor Identification === Company Name: AMETEK INC HAVEG DIV Address:900 GREENBANK RD Box:City:WILMINGTON State:DE ZIP:19808-5906 Country:US Phone:302-995-0400 CAGE:03200

Ingred Name:TALC (CONTAINING NO ASBESTOS) CAS:14807-96-6 RTECS #:WW2710000 Other REC Limits:NONE RECOMMENDED OSHA PEL:2 MG/M3 RDUST ACGIH TLV:2 MG/M3 RDUST; 9293

Ingred Name: FIBERGLASS Other REC Limits: NONE RECOMMENDED

Ingred Name:SILICON DIOXIDE

## (AMORPHOUS) CAS:67762-90-7 Other REC Limits:NONE RECOMMENDED

======================================
Routes of Entry: Inhalation:YES Skin:YES Ingestion:NO Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:ACUTE: EXCESSIVE CONTACT WITH SKIN MAY RESULT IN DERMATITIS IN SOME INDIVIDUALS. Effects of Overexposure:MILD IRRITATION OR REDNESS OF THE SKIN MAY OCCUR.
Medical Cond Aggravated by Exposure:NONE KNOWN.
======================================
First Aid:WASH OFF SKIN WITH MILD SOAP AND WATER. FOR EYES, FLUSH WITH COPIOUS QUANTITIES OF WATER. SEEK MEDICAL ATTENTION IF NEEDED.
======================================
Extinguishing Media:USE CARBON DIOXIDE OR DRY CHEMICAL FOR SMALL FIRES. USE FOAM FOR LARGE FIRES. WATER IN A FINE SPRAY CAN BE USED. Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AND PROTECTIVE CLOTHING SHOULD BE AVAILABLE FOR FIREMEN.
Unusual Fire/Explosion Hazard:NONE KNOWN.
======================================
Spill Release Procedures:SCOOP UP SPILLED MATERIA OR CONTAIN WITH ABSORBENT COMPOUND. DO NOT ALLOW SPILLED MATERIAL TO ENTER A WATERWAY AS PHENOLIC RESIN MAY BE LEACHED OUT. Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.
======================================
Handling and Storage Precautions:USE RUBBER GLOVES AND SAFETY GLASSES
WHEN HANDLING CEMENT AND HARDENER. STORE CEMENT IN CLOSED CONTAINERS.
Other Precautions:WHEN PREPARING SURFACES OF OLD HAVEG 41 EQUIPMENT, WHICH CONTAIN ASBESTOS, REFER TO OSHA ASBESTOS STANDARD 29 CFR 1910.1001 FOR PROPER COMPLIANCE.
======================================
Respiratory Protection:NONE Ventilation:MECHANICAL VENTILATION PREFERRED. Protective Gloves:RUBBER Eye Protection:SAFETY GLASSES WITH SIDE SHIELDS. Other Protective Equip

ment:ACID-RESISTANT CLOTHING RECOMMENDED. Work Hygienic Practices:GOOD PERSONAL HYGIENE METHODS RECOMMENDED. Supplemental Safety and Health NONE

HCC:N1 Spec Gravity:1.73 Solubility in Water:NEGLIGIBLE Appearance and Odor:BROWN COLORED, PUTTY-LIKE MATEIAL WITH CHARACTERISTIC PHENOLIC RESIN ODOR.

Stability Indicator/Materials to Avoid:YES STRONG MINERAL A CIDS. Stability Condition to Avoid:NONE KNOWN.

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE AND PHENOL.

Conditions to Avoid Polymerization:DO NOT USE AN EXCESSIVE AMOUNT OF HARDENER, OTHERWISE RAPID POLYMERIZATION WILL OCCUR.

Waste Disposal Methods:SMALL AMOUNTS OF THE UNCATALYZED CEMENT MAY BE CURED IN AN OVEN AT 250F., THEN BURIED IN A LANDFILL IN ACCORDANCE WITH FEDERAL, STATE AND LOCAL R EGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their parti

cular situation.