

CALGON CARBON CORP -- PBL ACTIVATED CARBON -- 6810-00-726-7944
===== Product Identification =====

Product ID:PBL ACTIVATED CARBON
MSDS Date:02/01/1990
FSC:6810
NIIN:00-726-7944
MSDS Number: BFMPL
=== Responsible Party ===
Company Name:CALGON CARBON CORP
Address:400 MEDIA DR
Box:717
City:PITTSBURGH
State:PA
ZIP:15205-1133
Country:US
Info Phone Num:415-572-9111
Emergency Phone Num:412-787-6700

CAGE
:1DA66
=== Contractor Identification ===
Company Name:BARNEBEY SUTCLIFFE CORP
Address:835 N CASSADY AVE
Box:City:COLUMBUS
State:OH
ZIP:43219-2203
Country:US
Phone:614-258-9501
CAGE:85335
Company Name:CALGON CARBON CORPORATION
Address:400 CALGON CARBON DR
Box:717
City:PITTSBURGH
State:PA
ZIP:15230-0717
Country:US
Phone:412-787-6700
CAGE:1DA66

===== Composition/Information on Ingredients =====

Ingred Name:ACTIVATED CARBON.
CAS:7440-44-0
RTECS #:FF5250100
Fraction by Wt: 100%
Ot

her REC Limits:NONE SPECIFIED
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:2 MG/M3 TDUST; 9293

===== Hazards Identification =====

LD50 LC50 Mixture:LD50 (ORAL, RAT) =>10G/KG
Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE-INGESTION:NON-TOXIC.
INHALATION:LC50 (RAT) IS >64.4 MG/M3. MAY CAUSE IRRITATION OF EYES
AND RESPIRATORY TRACT. SKIN:NON-IRRITATING. CHRONIC- NONE
KNOWN.
Effects of Overexposure:DISCOMFORT AND REDNESS OF EYE. COUGHING.
Medical Cond Aggravated by Exposure:NONE NOTICED.

===== First Aid Measures =====

First Aid:FIRST AID-INHALATION OF DUST, REMOVE TO FRESH AIR. EYE
CONTACT: FLUSH WITH WATER FOR 15 MINUTES. IF REDNESS OR IRRITATION
PERSIST CONTACT A DOCTOR. SKIN:WASH WITH SOAP AND WATER. INGESTION:
CONSULT A DOCTOR.

===== Fire Fighting Measures =====

Autoi
gnition Temp:Autoignition Temp Text:644F
Extinguishing Media:FLOOD WITH PLENTY OF WATER.
Fire Fighting Procedures:SINCE WET ACTIVATED CARBONS ABSOR OXYGEN, DO
NOT ENTER CLOSED VESSELS WITHOUT USING A SELF-CONTAINED BREATHING
APPARATUS.
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:COLLECT WITH BROOM AND SHOVEL OR VACUUM UP.
WET CARBON MAY BE COLLECTED WITH CARBON FINES.
Neutralizing Agent:NONE

=====

==== Handling and Storage =====

Handling and Storage Precautions:STORE AWAY FROM STRONG OXIDIZERS.
Other Precautions:NONE

==== Exposure Controls/Personal Protection =====

Respiratory Protection:DUSTMASK
Ventilation:NONE SPECIFIED BY MANUFACTURER.
Protective Gloves:DISPOSABLE GLOVES
Eye Protection:SAFETY GOGGLES.
Other Protective Equipment:NONE SPECIFIED BY MANUFACTURER.
Work Hygienic Practices:NONE SPECIFIED BY MANUFACTURER.
Supplemental Safety
and Health
NONE

==== Physical/Chemical Properties =====

HCC:N1
Spec Gravity:2.3
Solubility in Water:INSOLUBLE
Appearance and Odor:BLACK PARTICULATE SOLID, NO ODOR.
Percent Volatiles by Volume:00

==== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
CONTACT WITH STRONG OXIDIZERS SUCH AS OZONE, LIQUID OXYGEN, CHLORINE,
PERMANGANATE, MAY RESULT IN FIRE.
Stability Condition to Avoid:NONE
Hazardous Decompos
ition Products:NONE

==== Disposal Considerations =====

Waste Disposal Methods:PLACE IN SUITABLE CONTAINER AND DISPOSE OF BY
INCINERATION OR SEND TO A SANITARY LANDFILL.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims al

liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.