

BONDED PRODUCTS INC -- EPI-SEAL PASTE SPEC.2020 -- 8040-00-738-6429

=====
Product Identification
=====

Product ID:EPI-SEAL PASTE SPEC.2020

MSDS Date:01/01/1987

FSC:8040

NIIN:00-738-6429

Kit Part:Y

MSDS Number: BFMWB

=== Responsible Party ===

Company Name:BONDED PRODUCTS INC

Emergency Phone Num:(215) 696-9220

CAGE:3L885

=== Contractor Identification ===

Company Name:BONDED PRODUCTS INCORPORATED (C

ANCELLED 19092 -NEW)

Address:439 S BOLMAR ST

Box:39

City:WEST CHESTER

State:PA

ZIP:19382-4933

Country:US

CAGE:3L885

=====
Composition/Information on Ingredients
=====

Ingred Name:DURAMITE (CAS NO. 471-34-1)

CAS:471-34-1

RTECS #:FF9335000

Ingred Name:ALUMINUM (SARA III)

CAS:7429-90-5

RTECS #:BD0330000

OSHA PEL:15MG/M3 DUST/5 FUME

ACGIH TLV:10MG/M3 DUST; 9192

Ingred Name:ARALDITE 6004 (CAS NO. 25068-38-6)

CAS:25068-38-6

RTECS #:SL6475000

Ingred Name:SILICA, AMORPHOUS, DUST

CAS:112945-52-5
RTECS #:VV7310000
OSHA PEL:6 MG/M3
ACGIH TLV:10 MG/M3; 8990

=====
Hazards Identification
=====

Effects of Overexposure:POSSIBLE IRRITATION. STRONG SENSITIZER. AVOID VAP INHALE. PREVENT ALL SKIN & EYE CONTACT.

=====
First Aid Measures
=====

First Aid:SKIN:WASH AFFECTED AREAS W/SOAP & WATER.LAUNDER CONTAM CLOTHES BEFORE REUSE. EYES:FLUSH W/WATER FOR 15 MIN. INH:REMOVE TO FRESH AIR IMMED,GIVE O*2 OR ARTIF RESP IF NEC. BE EXAMINED BY A PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:>250F COC
Lower Limits:N/D
Upper Limits:N/D
Extinguishing Media:DRY CHEMICAL, FOAM, CO*2
Fire Fighting Procedures:WEAR NIOSH/MSHA APPRV RESPIR;COOL EXPOS CANS W/WATER SPRAY
Unusual Fire/Explosion Hazard:NO UNUSUAL HAZARDS. THE PRODUCT SHOULD BE HANDLED AS A COMBUSTIBLE MATERIAL.

=====
Accidental Release Measures
=====

Spil
I Release Procedures:REMOVE ALL SOURCES OF IGNITION. SOAK UP W/ABSORBENT MATERIAL OR SCRAPE UP. CLEAN UP CONTAMINATED AREA W/WATER.

=====
Handling and Storage
=====

Handling and Storage Precautions:PRACTICE GOOD CAUTION & PERSONAL HYGIENE TO AVOID SKIN & EYE CONTACT. STORE IN COOL PLACE. AVOID SPARKS & FLAMES.
Other Precautions:AVOID BREATHING VAPORS OF HEATED PRODUCT. DISCARD CONTAMINATED SHOES & OTHER LEATHER ARTICLES. MFR RECM NIOSH/MSH

A

APPROVED ORGANIC VAPOR RESPIRATOR, HOWEVER, SHOULD CONSULT SAFETY/IH

===== Exposure Controls/Personal Protection =====

Respiratory Protection: NIOSH/MSHA APPROVED RESPIRATORY PROT
REQD, CONSULT SAFETY OFF./I.H.

Ventilation: LOCAL EXHAUST; GENERAL MECHANICAL VENTILATION

Protective Gloves: IMPERVIOUS

Eye Protection: SPLASH PROOF GOGGLES

Other Protective Equipment: RUBBER APRONS OR COVERALLS

Supplemental Safety and Health

DATE OF PREP: 6/9/86. PART A OF A TWO PART KIT. KEY1:N1

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt: B.P. Text: N/D

Vapor Pres: N/D

Vapor Density: N/D

Spec Gravity: 1.12

Evaporation Rate & Reference: N/D

Solubility in Water: SLIGHT

Appearance and Odor: WHITE PASTE; CHARACTERISTIC ODOR

Percent Volatiles by Volume: N/D

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Hazardous Decomposition Products: CO &/OR CO*2

Conditions t

o Avoid Polymerization: EXCESS HEATING OVER LONG TIME
W/EXCESS OF CURING AGENT.

===== Disposal Considerations =====

Waste Disposal Methods: INCINERATE UNDER APPROVED CONDITIONS THAT MEET
FEDERAL, STATE & LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warr

ants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.