

3M COMPANY -- EC-801B,FUEL TANK SEALER,A-2 -- 8030-00-753-4598

===== Product Identification =====

Product ID:EC-801B,FUEL TANK SEALER,A-2

MSDS Date:01/01/1987

FSC:8030

NIIN:00-753-4598

MSDS Number: BFMZL

=== Responsible Party ===

Company Name:3M COMPANY

Address:3M CENTER

City:ST. PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1110

Emergency Phone Num:612-733-1110

CAGE:76381

=== Co

ntractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

Company Name:MINNESOTA MINING AND MFG CO, DBA 3M

Address:3M CENTER BLDG 224-5S-04

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:866-556 5712 / 612-733-1110

CAGE:76381

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETO

NE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 10%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200 PPM/300STEL 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:CARBON BLACK

CAS:1333-86-4

RTECS #:FF5800000

OSHA PEL:3.5 MG/M3

ACGIH TLV:3.5 MG/M3; 9192

Ingred Name:POLYSULFIDE RUBBER

Ingred Name:CALCIUM CARBONATE (MARBLE) (LIMESTONE)

CAS:1317-65-3

RTECS #:EV9580000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 9192

Ingred Name:PHENOLIC RESIN

=====

===== Hazards Identification =====

Effects of Overexposure:EYE: IRRIT.SKIN:DEFATTING/DERMATITIS.VAPORS:
HEADACHE,NAUSEA,DIZZINESS.

===== First Aid Measures =====

First Aid:EYE: FLUSH WITH WATER 15 MIN,CALL A PHYSICIAN. SKIN: WASH
WITH SOAP AND WATER.INHALATION: PROVIDE FRESH AIR.

===== Fire Fighting Measures =====

Flash Point:102F/38C (CC)

Lower Limits:1.8

Upper Limits:11.5

Extinguishing Medi

a:CO2,FOAM,DRY CHEM.

===== Accidental Release Measures =====

Spill Release Procedures:EXTINGUISH ALL IGNITION SOURCES.COLLECT
SPILLED MATERIAL.CLEAN UP RESIDUE AND PLACE IN METAL CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT,SPARKS AND OPEN
FLAME.USE ONLY WITH ADEQUATE VENTILATION TO REMOVE AND PREVENT
VAPOR BUILD UP.KEEP CONTAINER CLOSED.

Other Precautions:AVOID PROL
ONG BREATHING OF VAPORS AND PROLONGED OR
REPEATED SKIN CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN

Ventilation:LOCAL EXHAUST

Protective Gloves:RECOMMENDED

Eye Protection:CHEM GOGGLES

Supplemental Safety and Health

ADD INGRED: LITHOPONE & WATER. MFR ID CODE: 62-1287-9572-1. PKG SIZE:
1/2 PT. PART A OF 2 PART KIT. KEY1:J1.

===== Physical/Chemical
Properties =====

HCC:F4

Boiling Pt:B.P. Text:175F/79C

Vapor Pres:80

Vapor Density:2.5

Spec Gravity:1.4

Evaporation Rate & Reference:2.7 (ETHER)

Solubility in Water:SLIGHT

Appearance and Odor:BLACK LIQUID - SOLVENT ODOR

Percent Volatiles by Volume:10

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:CO,CO2,SULFUR,COMPOUND

===== Disposal Considerations =====

=====

Waste Disposal Methods:SEND TO HAZARDOUS WASTE MANAGEMENT FACILITY.DISPOSE IN A SECURE LANDFILL.EPA HAZARDOUS WASTE NUMBER D-001.LOCAL,STATE AND FEDERAL REGULATIONS. COMPLY.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.