View NSN Online: https://aerobasegroup.com/nsn/9150-00-753-4686

CASTROL INC., BRAY PRODUCTS DIV. -- BRAYCOTE 646 -- 9150-00-753-4686

Product ID:BRAYCOTE 646 MSDS Date:11/13/1990 FSC:9150 NIIN:00-753-4686 MSDS Number: BFNBT === Responsible Party === Company Name: CASTROL INC., BRAY PRODUCTS DIV. Address:16815 VON KARMAN AVE., SUITE 202 City:IRVINE State:CA ZIP:92714 Info Phone Num:714-660-9414 Emergency Phone Num:714-660-9414 CAG E:EO288 === Contractor Identification === Company Name: CASTROL INC., BRAY PRODUCTS DIV. Address:16715 VON KARMAN AVE., SUITE 230 City:IRVINE State:CA ZIP:92714 Country:US Phone:714-660-9414/ABROAD 202-4837616COLL CAGE:EO288 Company Name: CASTROL INDUSTRIAL NORTH AMERICA INC SPECIALTY PRODUCTS DIV Address:1001 WEST 31ST STREET Box:City:DOWNERS GROVE State:IL ZIP:60515-1280 Country:US Phone:800-621-2661/ FAX: 630-241-4140 CAGE:2R128

======= Composition/Information on Ingredients =======

Ingred Name:MFR REPORTED NO INGREDIENTS ON MSDS. FOLLOWING LIST IS TAKEN FROM MIL-L-46000B. MFR RECOMMENDED USE OF OIL MIST TLV. RTECS #:99999992Z Fraction by Wt: 8.0% Other REC Limits:0.MG/CUM OIL MIST

Ingred Name:LITHIUM STEARATE CAS:4485-12-5 Fraction by Wt: 7.7-8.3% ACGIH TLV:10 MG/CUM

Ingred Name:BIS(2ETHYLHEXYL) SEBACATE (LUBRICANT GRADE) CAS:122-62-3 RTECS #:VS1000000 Fraction by Wt: 88-90%

Ingred Name:DIISOPROPYL HYDROGEN PHOSPHATE CAS:1809-20-7 RTECS #:SZ7660000 Fraction b y Wt: FLASH POINT Unusual Fire/Explosion Hazard:NONE

Spill Release Procedures:WIPE UP OR ABSORB ON INERT MATERIAL. STORE IN CLOSED CONTAINERS PENDING DISPOSAL. Neutralizing Agent:NONE

Handling and Storage Precautions: STORE IN AREA AWAY FROM EXTREME HEAT AND/OR IGNITION SOURCES.

======= Exposure Controls/Personal Protection ==========

Re

spiratory Protection:NONE NORMALLY REQUIRED EXCEPT FOR OIL MIST. Ventilation:MECHANICAL (GENERAL) ACCEPTABLE LOCAL EXHAUST IF NEEDED. Protective Gloves:RUBBER/PLASTIC Eye Protection:SAFETY GLASSES Other Protective Equipment:NONE Supplemental Safety and Health

HCC:V6 Boiling Pt:B.P. Text:600F/316C Spec Gravity:0.93 Solubility in Water:NEGLIBLE Appearance and Odor:TAN COLORED,SEMI-FLUID LUBRICANT AGREEABLE ODOR.

Stability Indicator/Materials to Avoid:YES STRONG OXIDIZING AGENTS. Stability Condition to Avoid:HEAT, IGNITION SOURCES Hazardous Decomposition Products:CARBON MONOXIDE,CO*2 & OXIDES OF PHOSPHORUS.

Waste Disposal Methods:DISPOSE OF BY CONTROLLED INCINERATION OR METHOD IN COMPLIANCE W/LOCAL,STATE & FEDERAL REGULATIONS REGARDING HEALTH,AIR,& WATER POLLUTION.

Di

sclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.