View NSN Online: https://aerobasegroup.com/nsn/9150-00-753-4686

TENNECO CHEM, INC - INTERMEDIATES DIV -- ANDEROL SYNTHETIC LUBRICATING GREASE -- 9150-00-753-4686

| Product ID:ANDEROL SYNTHETIC LUBRICATING GREASE MSDS Date:01/01/1985 FSC:9150 NIIN:00-753-4686 MSDS Number: BFNBZ |
|--|
| === Responsible Party === Company Name:TENNECO CHEM, INC - INTERMEDIATES DIV Emergency Phone Num:301-778-1991 CAGE:GO844 === Contractor Identification = |
| |
| Company Name: TENNECO CHEM, INC - INTERMEDIATES DIV |
| CAGE:GO844 Company Name:TENNECO CHEMICALS INC ORGANIC AND POLYMERS DIV Address:TURNER PL Box:365 City:PISCATAWAY State:NJ ZIP:08854 |
| Country:US Phone:908-981-5000 |
| CAGE:99559 |
| ====================================== |
| Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT |
| ====================================== |
| Effects of Overexposure:PRLNGD/RPTD SKIN/EYE CNTCT MAY CAUSE IRRIT. |
| RLNGD BRTHNG OF CONC MIST AT HIGH TEMP MAY IRRIT LUNGS. |
| ====================================== |
| First Aid:SKIN: WASH W/SOAP & WATER. EYES: FLUSH IMMED W/PLENTY WATER 15 MIN. INH: REMOVE TO FRESH AIR. MFR STATES LOW DEGREE OF HAZ FOR THIS PROD. OBSERVE ORDINARY MEASURES OF PERSONAL HYGIENE. |
| |

Flash Point:>300F Extinguishing Media:WATER SPRAY, FOAM, CO*2, DRY CHEM Fire Fighting Procedures:NO NE

| Unusual Fire/Explosion Hazard:B | URNING MAY PRODUCE | E SM AMTS TOXIC FUMES. |
|---------------------------------|--------------------|------------------------|
| AVOID EXPOSURE. | | |

| ====================================== |
|--|
| Spill Release Procedures:SCRAPE UP & REMOVE TO DISPOSAL CNTNR. CLEAN UP AREA W/DETERGENT & WATER IF SLIPPERY. |
| ====================================== |
| Handling and Storage Precautions:ORDINARY CARE IN HANDLING CHEM |
| ====================================== |
| Respiratory Protec tion:PRLNGD/RPTD EXP TO CONC HOT FUMES/MIST, USE AIRLINE RESP Ventilation:MECH EXHST ACCEPTABLE Protective Gloves:YES Eye Protection:SAFETY GLASSES Other Protective Equipment:WASH CONTAM CLOTHING BEFORE REUSE Supplemental Safety and Health PROD NOT VOLATILE. SPEC GRAV IS 0.9-1.0. DROPPING PT IS 360-500F. |
| ====================================== |
| HCC:V6 Solubility in Water:NEGLIGIBLE Appearance and Odor:LIGHT TO DARK GREASE, SLIGHT MILD ODOR |
| ability and Reactivity Data ================================== |
| Stability Indicator/Materials to Avoid:YES STRONG OXIDANTS, ACIDS & BASES. MAY SOFTEN PLASTIC/PAINT Hazardous Decomposition Products:BURNING MAY PROD SM AMT TOXIC FUMES OR NITROGEN OXIDES |
| ====================================== |
| Waste Disposal Methods: BURY IN APPRVD LANDFILL. OBSERVE LOCAL, STATE, |

FED REG. DO NOT CONTAM ANY STREAMS, LAKES. PONDS.

Disclaimer (provided with this information by the compiling agen

cies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.