

MALLINCKRODT INC. SCIENCE PRODUCTS DIVISION -- METHYL ALCOHOL -- 6810-00-753-4783

=====
Product Identification
=====

Product ID:METHYL ALCOHOL

MSDS Date:04/06/1989

FSC:6810

NIIN:00-753-4783

MSDS Number: BFNCQ

=== Responsible Party ===

Company Name:MALLINCKRODT INC. SCIENCE PRODUCTS DIVISION

Address:PARIS BYPASS

Box:M

City:PARIS

State:KY

ZIP:40361

Country:US

Info Phone Num:314-982-5000

Emergency P

hone Num:314-982-5000

CAGE:62910

=== Contractor Identification ===

Company Name:MALLINCKRODT SPECIALTY CHEMICALS CO

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Phone:908-859-2151

CAGE:62910

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: >99%

Other REC Limits:NONE

OSHA PEL:S,200PPM/250STEL

ACGIH TLV:S,200PPM/250STEL; 93

EPA Rpt Qty:5000 LBS

DO

=====
===== Hazards Identification =====
=====

LD50 LC50 Mixture:LD50 ORAL RAT=5628MG/KG
Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:ACUTE:SIGNS & SYMPTOMS OF
OVEREXPOSURE. CHRONIC:MARKED IMPAIRMENT OF VISION AND ENLARGEMENT
OF THE LIVER HAS BEEN REPORTED.REPEATED OR PROLONGED EXPOSURE MAY
CAUSE SKIN IRRITATION.
Effects of Overexposure:EYES:IRR
ITANT,EYE
LESIONS;SKIN:DEFATTING,DRYNESS,CRACKING;SKIN ABSORPTION:SYMPTOMS
SIMILAR TO INHALATION;INHALATION:IRRITANT,TOXIC TO NERVOUS SYSTEM &
OPTIC NERVE,HEADACHE,DROWINESS,NAUSEA,VOMIT,BLURRE D
VISION,BLINDNESS,COMA,DEATH;INGESTION:SYMPTOMS SIMILAR TO
INHALATION.CAN CAUSE BLINDNESS.FATAL DOSE=100-125ML
Medical Cond Aggravated by Exposure:PERSONS WITH PRE-EXISTING SKIN
DISORDERS OR EYE PROBLEMS OR IMPAIRED LIVER OR KIDNEY FUNCTION.

=====
===== First Aid Meas
ures =====
=====

First Aid:EYES:FLUSH WITH PLENTY OF WATER.SEE DOCTOR
IMMEDIATELY;SKIN:REMOVE CONTAMINATED CLOTHING.WASH WITH PLENTY SOAP
& WATER.IF IRRITATION PERSISTS,SEE DOCTOR;INHALATION:REMOVE TO
FRESH AIR.GIVE CPR/OXYGEN IF NEEDED.SEE DOCTOR;INGESTION:GIVE 2
GLASSES OF WATER & INDUCE VOMIT IMMEDIATELY.SEE DOCTOR .NOTHING BY
MOUTH IF UNCONSCIOUS.

=====
===== Fire Fighting Measures =====
=====

Flash Point Method:CC
Flash Point:52.0F,
11.1C
Autoignition Temp:Autoignition Temp Text:725F
Lower Limits:6.7
Upper Limits:36
Extinguishing Media:USE CARBON DIOXIDE, FOAM, DRY CHEMICAL, OR WATER
FOG.
Fire Fighting Procedures:FIRE FIGHTERS SHOULD USE NIOSH APPROVED SCBA &
FULL PROTECTIVE EQUIPMENT WHEN FIGHTING CHEMICAL FIRE. USE WATER
SPRAY TO COOL NEARBY CONTAINERS EXPOSED TO FIRE.
Unusual Fire/Explosion Hazard:VAPOR HEAVIER THAN AIR.CAN TRAVE ALONG
GROUND

=====
===== Accidental Release Measures =====
=====

=====

Spill Release Procedures:REMOVE IGNITIO SOURCES.VENTILATE.WEAR RESPIRATORY PROTECTION & PROTECTIVE CLOTHING.ABSORB IN INERT MATERIAL AND PLACE IN APPROPRIATE DISPOSAL CONTAINER.

===== Handling and Storage =====

Handling and Storage Precautions:PROTECT AGAINST PHYSICAL DAMAGE.OUTSIDE OR DETACHED STORAGE PREFERRED.INSIDE STORAGE SHOULD BE FOR FLAMMABLE LIQUID.SEPARATE FROM OXIDIZING MATERIALS.

Other Precautions:STORAGE & USE AREAS SHOULD BE

NON-SMOKING.SPARKS-PROOF TOOLS & EXPLOSION-PROOF EQUIPMENT SHOULD BE USED IN THE STORAGE & HANDLING AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH EXPOSURE OF CONCERN.

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves:RUBBER,NEOPRENE.

Eye Protection:GOGLES (DO NOT WEAR CONTACT LENSES)

Other Protective Equipment:RUBBER BOOTS,APRON OR COVERALLS. EYEWASH STATION AND SAFETY SHOWER.

Work Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.REMOVE LAUNDER CONTAMINATED CLOTHING.

Supplemental Safety and Health NONE

===== Physical/Chemical Properties =====

HCC:F5

Boiling Pt:=64.4C, 148.F

Melt/Freeze Pt:=-97.8C, -144.F

Vapor Pres:97

Vapor Density:1.1

Spec Gravity:0.8

Evaporation Rate & Reference:5.9 (BUTYL ACETATE=1)

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR, COLORLESS LIQUID, CHAR. ODOR

Percent Volatiles by Volume:10

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid: YES

STRONG OXIZING AGENTS. WILL ATTACK SOME FORMS OF
PLASTICS, RUBBER, COATING. MAY REACT WITH METALLIC AL TO FORM H²
GAS.

Stability Condition to Avoid: HIGH TEMPERATURES, SPARKS, AND OPEN FLAMES

Hazardous Decomposition Products: CO, CO², FORMALDEHYDE

=====
Disposal Considerations
=====

Waste Disposal Methods: DISPOSE AS HAZARDOUS WASTE IN A RCRA APP
ROVED

FCILITY. DO NOT FLUSH TO SEWER. COMPLY WITH ALL APPLICABLE
FEDERAL, STATE & LOCAL ENVIRONMENTAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.