

BAKER SEALANTS -- MIL-A-13881,THREAD CPD -- 8030-00-753-4953

=====
Product Identification
=====

Product ID:MIL-A-13881,THREAD CPD

MSDS Date:01/01/1987

FSC:8030

NIIN:00-753-4953

MSDS Number: BFNFL

=== Responsible Party ===

Company Name:BAKER SEALANTS

Emergency Phone Num:210-333-6986

CAGE:EO611

=== Contractor Identification ===

Company Name:BAKER SEALANTS

CAGE:EO611

Company Name:BAKER SEALANTS AND

COATINGS CO

Address:234 SUYDAM AVE

Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306

Country:US

Phone:201-333-6986

CAGE:34094

=====
Composition/Information on Ingredients
=====

Ingred Name:MICA - SILICATES (< 1% CRYSTALLINE SILICA)

CAS:12001-26-2

RTECS #:VV8760000

Fraction by Wt: 60%.

OSHA PEL:20 MPPCF

ACGIH TLV:3 MG/M3 RDUST; 9293

Ingred Name:REFINED PETROLEUM OIL

Fraction by Wt: 40%.

=====
Fire Fighting Measures
=====

Flash Point:7599F COC

Ex

tinguishing Media:DRY FORE EXTINGUISHER

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP IN NORMAL FASHION AND DISPOSE NORMALLY

===== Handling and Storage =====

Handling and Storage Precautions:MFG STATES PRODUCT IS NOT HAZARDOUS

===== Exposure Controls/Personal Protection =====

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:N1

Spec Gravity:1.22

Percent Volatiles by Volume:0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:NORMAL WAY

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, w
arrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.