Product ID:PR-1422 A-2 (W) MSDS Date:01/01/1987

FSC:8030

NIIN:00-753-5009

Kit Part:Y

MSDS Number: BFNJZ === Responsible Party === Company Name:COURTAULDS

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:800-424-9300 CHEMTREC/800-22

8-5635

CAGE:83574

=== Contractor Identification ===

Company Name: PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA ZIP:91209 Country:US

Phone:818-240-2060

CAGE:83574

====== Composition/Information on Ingredients ========

Ingred Name: CALCIUM DICHROMATE

CAS:14307-33-6 RTECS #:HX7630000 Fraction by Wt: 4%

OSHA PEL:C, 0.1 MG/M3 (CRO3) ACGIH TLV:0.05 MG/M3 (CR);8990

Ingred Name: TOLUENE (SARA III)

CAS:108-88-3 RTECS #

ACGIH TLV:50 PPM; 9293 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS
Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III) CAS:78-93-3 RTECS #:EL6475000 Fraction by Wt: 4% Other REC Limits:NONE RECOMMENDED OSHA PEL:200 PPM ACGIH TLV:200 PPM/300STEL;9394 EPA Rpt Qty:5000 LBS DOT Rpt Qty:5000 LBS
Ingred Name:DIMETHYLACETAMIDE Fraction by Wt: 2% ACGIH TLV:10PPM
========== Hazards Identification ============
Effec ts of Overexposure:HDACH; POSS SKIN IRRIT.
======================================
First Aid:SKIN:WASH THOROUGHLY WITH SOAP & WATER. EYES:WASH OUT IMMED W/LG AMOUNT OF WATER; SEE A PHYSICIAN. INHAL: REMOVE TO FRESH AIR.
======================================
Flash Point:23F PMCC -5C Lower Limits:1.8 Upper Limits:10.0 Extinguishing Media:USE ANY EXTING APPRVD FOR CL B FIRES. Unusual Fire/Explosion Hazard:MAY EMIT POTENTIALLY TOXIC VAPORS.
========= Accidental Release Measures ==========
Spill Release Procedures:WIPE UP EXCESS W/RAGS OR PAPER TOWELS; CLEAN AREA W/MEK.
=========== Handling and Storage =============
Handling and Storage Precautions: KEEP IN CLOSED CONTAINERS IN SHELTERED AREA. KEEP AWAY FROM HEAT, SPARKS & OPEN FLAME. AVOID PROLNG OR REPEATED SKN CONTCT AND BREATHING OF VAPORS.
====== Exposure Controls/Personal Protection ========
Respirat

:XS5250000

Fraction by Wt: 4% OSHA PEL:200 PPM/150 STEL

ory Protection: AIR-SUPPLIED RESPIR IN ENCLOSE AREAS.

Ventilation: ADEQ TO MINIMIZE VAPORS Protective Gloves: POLY/PROTCT HAN

Waste Disposal Methods:DISPOSE OF CURED MATERIAL IN NORMAL TRASH. DO NOT INCINERATE.

======= Disposal Considerations ============

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.