View NSN Online: https://aerobasegroup.com/nsn/6550-00-764-4729

EM DIAGNOSTIC SYSTEMS, INC -- FAST STAIN; CAT#65026, B4128 -- 6505-00-764-4729

======== Product Identification ============

Product ID:FAST STAIN;CAT#65026,B4128

MSDS Date:01/01/1987

FSC:6505

NIIN:00-764-4729

MSDS Number: BFNVB === Responsible Party ===

Company Name: EM DIAGNOSTIC SYSTEMS, INC

Address:111 WOODCREST RD

City:CHERRY HILL

State:NJ

ZIP:08034-0395 Country:US

Emergency Phone Num:NONE

CAGE:OGDF9

=== Co

ntractor Identification ===

Company Name: E M SCIENCE DIV OF E M INDUSTRIES INC

Address:480 DEMOCRAT ROAD

Box:70

City:GIBBSTOWN

State:NJ ZIP:08027 Country:US

Phone:800-222-0342/609-423-6300

CAGE:63612

Company Name: EM DIAGNOSTIC SYSTEMS, INC

Address: 480 DEMOCRATE ROAD

City:GIBBSTOWN

State:NJ ZIP:08027

Phone:(609) 423-6300

CAGE:OGDF9

======= Composition/Information on Ingredients ========

Ingred Name: METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000 OSHA PEL:S,200PP DOT Rpt Qty:5000 LBS Ingred Name: UNIDENTIFIED COMPONENTS ACGIH TLV:NOT SPECIFIED ========== Hazards Identification =============== Effects of Overexposure:INGEST/INHLE:HEADACHE,DROWSINESS,IRRIT OF EYES, BLURRED VISION DEATH; SKIN: IRRITATION; EYES: BLINDNESS First Aid: INHALE: REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED; EYES/SKIN: FLUSH W LG AM TS H*20 FOR 15 MIN; INGEST: RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE. Flash Point:54F/12C (C.C.) Lower Limits:6.0 Upper Limits:36.5 Extinguishing Media:CO*2,FOAM,DRY CHEMICAL Fire Fighting Procedures: USE NIOSH APPROVED SCBA WITH FULL PROTECTION IF NEEDED Unusual Fire/Explosion Hazard: WHEN EXPOSE TO FLAME IT HAS MODERATE ACTION. ======= Acci dental Release Measures ========= Spill Release Procedures: USE PROPER PERSONAL PROTECTION; REMOVE ALL IGNITION SOURCES.USE SUITABLE ABSORBENT MATERIAL AND RECOVER FOR PROPER DISPOSAL. ============ Handling and Storage =========================== Handling and Storage Precautions: STORE IN COOL, DRY AND WELL VENTILATED. KEEP CONTAINER CLOSED WHEN NOT IN USE.KEEP AWAY/HEAT, SPARKS AND OPEN FLAME.WASH THOROUGHLY AFTER EACH USE. Other Precautions: MAY BE FATAL OR CAUSE B

M/250STEL

EPA Rpt Qty:5000 LBS

ACGIH TLV:S,200PPM/250STEL; 93

LINDNESS IF SWALLOWED.AVOID SKIN AND EYES CONTACT.DO NOT BREATHE VAPORS. ===== Exposure Controls/Personal Protection ======== Respiratory Protection: USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS. Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV. Protective Gloves: IMPERVIOUS Eye Protection: SAFETY/CHEM GOGGLES Other Protective Equipment: FULL PROTECTIVE CLOTHING, SAFETY SHOWER, EYE WASH STATION Supplemental Safety and Health **MSDS DATED 8/16/85** ======== Ph ysical/Chemical Properties ========= HCC:F2 Boiling Pt:=64.C, 147.2F Vapor Pres:100 Vapor Density:1.11 Spec Gravity:0.791 Evaporation Rate & Reference: 5.9 (BUT ACET=1) Solubility in Water:MISCIBLE Appearance and Odor: CLEAR LIQUID, SLIGHT ALCOHOLIC ODOR ======== Stability and Reactivity Data =========== Stability Indicator/Materials to Avoid:YES **OXIDIZERS** Stability Condition to Avoid: HEAT AND FLAME Hazardous Decomposition Products: TOXIC GASSES AND VAPORS SUCH AS

FORMLADEHYDE AND CO.

======= Disposal Considerations ==========

Waste Disposal Methods:DISPOSE OF COLLECTED MATERIAL IN ACCORDANCE WITH LOCAL, STATE AND FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all

liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.