

SHERWIN INCORPORATED -- DR61 CLEANER/REMOVER -- 6850-00-782-2740

=====  
Product Identification  
=====

Product ID:DR61 CLEANER/REMOVER

MSDS Date:01/01/1987

FSC:6850

NIIN:00-782-2740

Kit Part:Y

MSDS Number: BFPNQ

=== Responsible Party ===

Company Name:SHERWIN INCORPORATED

Address:5530 BORWICK AVE

City:SOUTH GATE

State:CA

ZIP:90280-7402

Country:US

Info Phone Num:213-861-6324

Emergency Phone Num:213-86

1-6324

CAGE:EO073

=== Contractor Identification ===

Company Name:SHERWIN INC.

Address:5530 BORWICK AVE.

City:SOUTH GATE

State:CA

ZIP:90280-7402

Country:US

Phone:562-861-6324/FAX 923-8370

CAGE:21405

Company Name:SHERWIN INCORPORATED

Address:5530 BORWICK AVENUE

Box:City:SOUTH GATE

State:CA

ZIP:90280

Country:US

Phone:562-861-6324

CAGE:EO073

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYL CHLOROFORM (1,1,1-TRICHLOROETHANE) (SARA III)

CAS:71-55-6

RTECS #:KJ29

75000  
Fraction by Wt: 96.0%  
OSHA PEL:350 PPM/450 STEL  
ACGIH TLV:350 PPM/450STEL;9192  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS  
Ozone Depleting Chemical:1

Ingred Name:1,2-BUTYLENE OXIDE (SARA III)  
CAS:106-88-7  
RTECS #:EK3675000  
EPA Rpt Qty:1 LB  
DOT Rpt Qty:1 LB

Ingred Name:1,4-DIOXANE (DIETHYLENE DIOXIDE) (SARA III)  
CAS:123-91-1  
RTECS #:JG8225000  
OSHA PEL:S, 100 PPM  
ACGIH TLV:S, 25 PPM; 9293  
EPA Rpt Qty:100 LBS  
DOT Rpt Qty:100 LBS

Ingred Name:NITROMETHANE  
CAS:75-52-5  
RTECS #:PA9800000  
OSHA PE  
L:100 PPM  
ACGIH TLV:100 PPM; 9192

Ingred Name:ISOBUTANE (66% BY VOLUME APPROX) AS PROPELLANT (PER MFR)  
CAS:75-28-5  
RTECS #:TZ4300000

=====  
===== Hazards Identification =====

Effects of Overexposure:EYES:IRRITATION,CORNEAL  
INJURY.SKIN:IRRITANT,DERMATITIS.INHAL:DIZZINESS,DROWSINESS.CVS  
DEPRESSION.

=====  
===== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF  
NEED;EYES/SKIN:FLUSH W LG AMTS H\*20

FOR 15 MIN;INGEST:RINSE MOUTH;  
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER  
SYMPTOMS OF OVEREXPOSURE.

===== Fire Fighting Measures =====

Flash Point:NONE  
Lower Limits:7.5  
Upper Limits:15.0  
Extinguishing Media:WATER FOG  
Fire Fighting Procedures:USE NIOSH APPROVED SCBA FOR FIRE FIGHTING.USE  
WATER TO COOL  
Unusual Fire/Explosion Hazard:VAPORS DECOMPOSE TO HAZARDOUS PRODUCTS AT  
HIGH TEMPERATURES.

===== Accidental Re  
lease Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTIVE EQUIPMENT.DIKE  
THE AREA.USE ABSORBENT MATERIALS AND RECOVER IN AN APPROVED  
CONTAINER FOR DISPOSAL.

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY PLACE.PROVIDE  
ADEQUATE VENTILATION.KEEP CONTAINER CLOSED WHEN NOT IN USE.  
Other Precautions:AVOID SKIN AND EYES CONTACT.DO NOT SMOKE IN PRESENCE  
OF VAPORS.WASH THOROUGHLY A  
FTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:USE NIOSH-APPROVED CANNISTER RESPIRATOR/OR SCBA  
IN CONFINED AREAS.  
Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN