View NSN Online: https://aerobasegroup.com/nsn/6850-00-782-2740

Product ID:ZL-22A ZYGLO PENETRANT(PRE 1/87-SEE SUPPL) MSDS Date:04/02/1980 FSC:6850 NIIN:00-782-2740 Kit Part:Y **MSDS Number: BFPNY** === Responsible Party === Company Name: MAGNAFLUX CORPORATION Address:7300 W.LAWRENCE AVENUE City:CHICAGO State:IL ZIP:60656-3504 Country:US Info Phone Num:312-867-8000 Emergency Phone Num:312-867-8000 Preparer's Name: BRUCE C. GRAHAM CAGE:37676 === Contractor Identification === Company Name: ILLINOIS TOOL WORKS INC MAGNAFLUX DIV Address:3624 WEST LAKE AVENUE Box:City:GLENVIEW State:IL ZIP:60025 Country:US Phone:847-657-5300/ CAGE:37676

Ingred Name:PETROLEUM HYDROCARBONS Fraction by Wt: 69.0% ACGIH TLV:200 PPM

Ingred Name: DIPHENYL OCTYL PHOSPHATE-ETHOXYLATED OCTYLPHENOL

Fraction by Wt: 24.0%

Ingred Name:ORGANIC FLUORESCENT DYE Fraction by Wt: 5.0%

Ingred Name:CARBON DIOXIDE CAS:124-38-9 RTECS #:FF6400000 Fraction by Wt: 2.0% OSHA PEL:5000 PPM ACGIH TLV:5000PPM/30000STEL;93

======================================
Effects of Overexposure:DIZZINESS,DROWSINESS,NAUSEA
======================================
<ul> <li>First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG DIFF GIVE OXYGEN. EYE:IM</li> <li>MED FLUSH W/PLENTY OF WATER. SKIN:WASH W/SOAP&amp;WATER. RMV CONTAM CLTHG&amp;SHOES. INGEST:INDUCE VOMIT. RPT UNTIL VOMIT IS C LEAR. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.</li> </ul>
======================================
Flash Point:N/R (AEROSOL) Lower Limits:1.0 Upper Limits:6.0

Extinguishing Media:NONE SPECIFIED BY THE MFR.USE SCBA FOR FIREFIGHTING Fire Fighting Procedures:AEROSOL CAN MAY BURST AT TEMPERATURES ABOVE 130 DEGREES F.

Spill Release Procedures: FILLED CAN ONLY CONTAINS 300 MI OF MATERIAL WHICH CAN BE WIPED UP WITH RAGS ETC.

 Handling and Storage Precautions:STORE AWAY FM HEAT IN UPRIGHT
 POSITION. PROTECT CONTAINERS FROM PHYSICAL DAMAGE.
 Other Precautions:WASH THOROUGHLY AFTER HANDLING TO PREVENT SKIN IRRITATION.

======= Exposure Controls/Personal Protection ==========

Respiratory

Protection:RESPIRATOR WITH FILTER CARTRIDGE IF SPRAYED IN CLOSE AREA Ventilation:SPRAY BRTH OR LAB FUME HOOD IS PREFERRED Protective Gloves:RUBBER Eye Protection:SAFETY GOGGLES Work Hygienic Practices:WASH THOROUGHLY AFTER USE OF:ZL-22A. Supplemental Safety and Health NSN IS FOR KIT OF 3 PARTS;PER MIL-I-25135,REV "C",NSN WAS FOR GRUOP VII KIT CONTAINING PENETRANT(ZL-22A),DEVELOPER(SKD-NF OR ZP-9B),& REMOVER(SKC-NF/ZC-7);THIS ENTRY OF ZL-22A;UNDER NEW SPEC,REV "D",N SN IS CALLED F OR TYPE I,METH C,LVL 3;PNI-A TO D DESCRIBE OLD PARTS;NEW PARTS OF THE KIT UNDER PNI-E THRU H;KEY1:J7.

HCC:V2 Boiling Pt:B.P. Text:400F(LIQ) Spec Gravity:0.97 OF LIQUID Solubility in Water:NEGLIGIBLE Appearance and Odor:GREASY, OILY LIQUID. Percent Volatiles by Volume:2.0

Stability Indicator/Materials to Avoid:YES MAY DISSOLVE,SOFTEN OR STAIN RUBBERS & P LASTICS. Stability Condition to Avoid:DO NOT HEAT ABOVE 130F Hazardous Decomposition Products:NONE

Waste Disposal Methods:DISPOSE OF I/A/W ALL LOCAL, STATE, AND FEDERAL REGULATIONS.SPECIAL CARE IS REQUIRED FOR DISPOSAL OF PRESSURIZED AEROSOL CANS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.